

## Product Overview

### CAT93C86: EEPROM Serial 16-Kb Microwire

For complete documentation, see the data sheet.

The CAT93C86 is a 16-kb Serial EEPROM memory device which is configured as either registers of 16 bits (ORG pin at  $V_{CC}$ ) or 8 bits (ORG pin at GND). Each register can be written (or read) serially by using the DI (or DO) pin. The CAT93C86 features a self-timed internal write with auto-clear. On-chip Power-On Reset circuit protects the internal logic against powering up in the wrong state.

### Features

- High Speed Operation: 3 MHz (5 V)
- 1.8 V to 5.5 V Supply Voltage Range
- Selectable x8 or x16 Memory Organization
- Self-timed Write Cycle with Auto-clear
- Sequential Read
- Hardware and Software Write Protection
- Power-up Inadvertent Write Protection
- Low Power CMOS Technology
- Program Enable (PE) Pin
- 1,000,000 Program/Erase Cycles

For more features, see the data sheet

### Part Electrical Specifications

Product	Compliance	Status	Type	Density	Organization	Data Transmission Standard	$f_{cycle}$ Max (kHz)	$t_{ACC}$ Max ns	$V_{CC}$ Min (V)	$V_{CC}$ Max (V)	$I_{standby}$ Max ( $\mu$ A)	$I_{act}$ Max (mA)	T Min ( $^{\circ}$ C)	T Max ( $^{\circ}$ C)	Package Type
CAT93C86VI-G	Pb-free Halide free	Active	Serial	16 kb	2k x 8	Micro Wire	2000	150	1.8	5.5	10	3	-40	85	SOIC-8
CAT93C86VI-GT3	Pb-free Halide free	Active	Serial	16 kb	2k x 8	Micro Wire	2000	150	1.8	5.5	10	3	-40	85	SOIC-8
CAT93C86XI-T2	Pb-free Halide free	Active	Serial	16 kb	2k x 8	Micro Wire	2000	150	1.8	5.5	10	3	-40	85	SOIC-8

For more information please contact your local sales support at [www.onsemi.com](http://www.onsemi.com).

Created on: 12/5/2018

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ON Semiconductor:](#)

[CAT93C86VI-G](#)