



Quality Products. Service Excellence.

Economy Server Cabinet RB-DC Series

2,300 lbs Weight Capacity



Features

- Constructed in 16-gauge steel.
- Meets PCI DSS (Payment Card Industry Data Security Standard) compliance requirements.
- Inside rear of cabinet includes two (2) toolless PDU cable trays for cable management and industry-standard vertical PDU installation.
- Cabinet doors feature a minimum 65% airflow perforation pattern that meets or exceeds equipment manufacturer requirements.
- Top panel is easily removable for cable installation. The generous cable access panels make it easy to install top panel without affecting installed cabling.
- Ships with doors and rails fully assembled ready for installation on-site. Side panels come packaged inside cabinet for on-site installation.
- Built in joining kit speeds up baying of multiple RB-DC cabinets within a row.

RACK BASICS®



Specifications

- Server Cabinet includes:
 - One (1) locking front cabinet door with curved surface for added stability.
 - One (1) locking pair of split rear cabinet door making access easier in tight spaces.
 - Two (2) pairs of split, locking and removable side panels. Split panels are more versatile for removing.
 - Two (2) pairs of 19in EIA-310-D compliant square hole punched rails with rack unit markings.
 - Rails easily adjust in depth in 1/4" increments.
 - Starter pack of (50) M6 screws, cage nuts and washers included.
 - For 10-32 hardware see the **CAGKIT Series**.
 - Two (2) toolless PDU cable tray.
 - Six (6) hinged plastic cable grommets on top panel.
 - One (1) removable top panel with numerous cable grommets.
 - Four (4) adjustable leveling feet.
 - Four (4) recessed casters allows for clearance through a standard height doorway.
 - Casters can be removed.
 - Casters are for moving an empty cabinet into place, not to support equipment load.
 - Generous bonding locations provided on frame.
 - Open bottom
- Finished in textured black powder paint.
- Tested to 2,300 lbs (1050 kg) of equipment load.
- Rated for up to 660 lbs (300 kg) rolling caster load rating.
- RoHS Compliant.

Part of the Rack Basics® line of economy rack solutions.

Gallery



Accessories

- Cabinet Handles with Combination Lock
- Horizontal Finger Cable Manager
- Horizontal Hinged Cable Manager
- Universal Rack Shelf
- Four Post Mounting Sliding Shelf
- Outlet Strips
- Mounting Hardware
- Horizontal Ring Cable Manager
- Horizontal Lacing Strip
- Adjustable Depth Shelf
- Rack Mount Locking Storage Drawer
- Sliding Keyboard Shelf
- Rack Panels

Part No.	Overall Dimensions			Rack Units	Mounting Dimensions		
	Height	Width	Depth		Height	Width	Usable Depth
RB-DC2442	47.14	23.62	42.74	24U	42.00	19.00	37.00
RB-DC4242	78.64	23.62	42.74	42U	73.50	19.00	37.00
RB-DC4842	89.14	23.62	42.74	48U	84.00	19.00	37.00

Overall height includes leveling feet and casters. Data subject to change without notice

Tags: **Server Rack Enclosure Cabinet, Rack Enclosure, Network Shelter, Net Shelter**

Data subject to change without notice

© 2018. Hammond Manufacturing Ltd. All rights reserved.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Hammond](#):

[RB-DC4242](#) [RB-DC4842](#) [RB-DC2442](#)