








6. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI.




△6	OBSOLETE	W/O	TAPE & REEL	YELLOW	GREEN	1.27um[50u"]	3-1734324		
						0.762um[30u"]	3-1734324		
						0.381um[15u"]	3-1734324		
						0.152um[6u"]	3-1734324		
	OBSOLETE			GREEN	YELLOW	1.27um[50u"]	3-1734324		
						0.762um[30u"]	3-1734324		
						0.381um[15u"]	3-1734324		
						0.152um[6u"]	3-1734324		
△6	OBSOLETE	W/	TRAY	YELLOW	GREEN	1.27um[50u"]	2-1734324		
						0.762um[30u"]	2-1734324		
						0.381um[15u"]	2-1734324		
						0.152um[6u"]	2-1734324		
						GREEN	YELLOW	1.27um[50u"]	2-1734324
								0.762um[30u"]	2-1734324
								0.381um[15u"]	2-1734324
								0.152um[6u"]	2-1734324
		RIB	PACKAGE	POSITION 2 INDICATOR	POSITION 1 COLOR	MIN. GOLD THICKNESS	PART NUMBER		


DIMENSIONS: mm	
	
MATERIAL	


TOLERANCES UNLESS OTHERWISE SPECIFIED	
0 PLC	$\pm -$
1 PLC	± 0.3
2 PLC	± 0.2
3 PLC	± 0.15
4 PLC	$\pm -$
ANGLES	$\pm 3'$
FINISH	

TE Connectivity

NAME				MODULAR JACK CONNECTOR RJ45 WITH LED, 8P8C, SHIELDED TAB DOWN, DIP TYPE, H=11.3mm			
SIZE	CAGE CODE	DRAWING NO			RESTRICTED		
A3	00779	C-1734324			—		
SCALE				SHEET		2 OF 7	
				REV		A5	








- 1.1 HOUSING: PA9T, WITH 30% GF, UL94 V-0, BLACK COLOR.
- 1.2 INSERT HOUSING: PA46, WITH 30% GF, UL94 V-0, BLACK COLOR.
- 1.3 CONTACTS: PHOSPHOR BRONZE.
- 1.4 SHELL: BRASS.
- 1.5 LED SOLDER TAIL: STEEL.
- 1.6 MYLAR: SILICONE POLYMER.

2.1 CONTACTS: (SEE TABLE) GOLD PLATED ON CONTACT AREA.
GOLD FLASH ON SOLDER TAIL.
1.27um [50u"] MIN. NICKEL UNDERPLATED OVERALL.

2.2 SHELL: 0.508um [20u"] MIN. NICKEL PLATED.

2.3 LED: 1.02um [40u"] COPPER UNDERPLATED OVERALL.
1.27um [50u"] NICKEL OVERALL.
1.27um [50u"] SILVER ON BONDING AREA.
2.54um [100u"] BRIGHT-TIN ON SOLDER AREA.

5. WAVE SOLDER CAPABLE TO 265°C PER TE SPEC 109-202, CONDITION B.



TAPE & REEL	GREEN/ ORANGE	YELLOW	1.27um[50u"]	6-1734324-
			0.762um[30u"]	6-1734324-
			0.381um[15u"]	6-1734324-
			0.152um[6u"]	6-1734324-
TRAY			1.27um[50u"]	6-1734324-
			0.762um[30u"]	6-1734324-
			0.381um[15u"]	6-1734324-
			0.152um[6u"]	6-1734324-
PACKAGE	POSITION 2	POSITION 1	MIN. GOLD THICKNESS	PART NUMBER
	INDICATOR	COLOR		

DWN

CHK

APVD

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

DIMENSIONS: mm	
	
MATERIAL	

TOLERANCES UNLESS OTHERWISE SPECIFIED	
0 PLC	$\pm .-$
1 PLC	± 0.3
2 PLC	± 0.2
3 PLC	± 0.15
4 PLC	$\pm .-$
ANGLES	$\pm 3'$
FINISH	

TE Connectivity

MODULAR JACK CONNECTOR
RJ45 WITH LED, 8P8C, SHIELDED
TAB DOWN, DIP TYPE, H=11.3mm

RESTRICTED TO

9(C)-1734324

CUSTOMER DRAWING

SCA

SHEET

5 OF 7

REV $\Delta 5$

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.



COPYRIGHT 2010

BY TYCO ELECTRONICS CORPORATION.

LOC
DW

DIST

REVISIONS

P

LTR


DESCRIPTION

DATE


DWN

APVD

SEE SHEET 1.





DETAIL C




SEE DETAIL C


TRAY



BAG

20 DESICCATING AGENTS
AT LEAST

BOX




LABEL

13Kg	11.1Kg	80	33	2640	6-1734324-1~4
					5-1734324-X
					7-1734324-X
					4-1734324-X
					2-1734324-X
					1734324-X
14.5Kg	12.5Kg	90			
GROSS WEIGHT	NET WEIGHT	PCS /TRAY	TRAY /BOX	PCS /BOX	PART NUMBER

NOTES:

1. MATERIAL:
TRAY: PVC.
BOX: CORRUGATED FIBER.
2. DIMENSION: SEE DRAWING
3. QUANTITY: SEE TABLE
4. WEIGHT: SEE TABLE

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

MATERIAL

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC ±
1 PLC ±0.3
2 PLC ±0.2
3 PLC ±0.15
4 PLC ±
ANGLES ± 3°

FINISH

DWN

CHK

APVD

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

STE

TE Connectivity

NAME

MODULAR JACK CONNECTOR
RJ45 WITH LED, 8P8C, SHIELDED
TAB DOWN, DIP TYPE, H=11.3mm

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C=1734324

SCALE

SHEET

6 of 7

REV A5

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT 2010 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC
DW

DIST

REVISIONS

P

LTR



DESCRIPTION

DATE

DWN



APVD

SEE SHEET 1.





NOTE:

1. EACH BAG SHALL BE INCLUDED:
*DESICCANT
2. PEELING STRENGTH: $0.1 \sim 1.3N$ ($1 \sim 130$ GRAMS) FOR $12 \sim 56mm$ WIDE CARRIER TAPES
3. PEELING SPEED: 300mm/MINUTES.
4. PACKAGING MATERIAL:
 - 4.1 COVER TAPE—COMPOSITE OF POLYETHYLENE TEREPHTHALATE (PET)
 - 4.2 CARRIER—POLYSTYRENE (PS)
 - 4.3 CARRIER REEL—POLYSTYRENE



USER DIRECTION OF UNREELING

SEE DETAIL C



8.5KG	6.1KG	180	8	1440	6-1734324-5~8
					3-1734324-X
					1-1734324-X
GROSS WEIGHT	NET WEIGHT	PCS /REEL	REEL /BOX	PCS /BOX	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mmTOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	$\pm .$
1 PLC	± 0.3
2 PLC	± 0.2
3 PLC	± 0.15
4 PLC	$\pm .$
ANGLES	$\pm 3^{\circ}$

MATERIAL

FINISH

DWN

CHK

APVD

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

STE

TE Connectivity

NAME

MODULAR JACK CONNECTOR
RJ45 WITH LED, 8P8C, SHIELDED
TAB DOWN, DIP TYPE, H=11.3mm

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C=1734324

SCALE

SHEET

7 of 7

REV A5

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1734324-5](#)