


DO NOT SCALE

DIMENSIONS IN mm

METRIC



THIRD ANGLE

PROJECTION



NOTES:

- 1 MAX. CABLE TIE WIDTH 3,6.
- 2 TENSILE STRENGTH 210 kPa
- 3 APPL. TEMP. RANGE +5 - +50°C.



BLACK		POLYAMIDE 6/6		2-100733-2	100
NATURAL		POLYAMIDE 6/6		2-100733-1	100
FINISH		MATERIAL		PARTNUMBER	QTY
-	-	-	-	CUSTOMER DRAWING FOR REFERENCE ONLY WILL NOT BE UPDATED © COPYRIGHT 19- BY AMP HOLLAND B.V. ALL INTERNATIONAL RIGHTS RESERVED. AMP PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN AND/OR PATENTS PENDING. THIS DRAWING IS UNPUBLISHED RELEASED FOR PUBLICATION , 19-	
-	-	-	-		
-	-	-	-		
-	-	-	-		
-	-	-	-		
-	-	-	-	AMP AMP HOLLAND B.V. 's-Hertogenbosch, The Netherlands.	
0	H-9856	R.D.	RV	NAME MOUNTING BASE.	
LTR.	REVISION RECORD	DR.	CHK.	DATE	
DR.:	R. DAAMEN	CHK.:	R. VOS.	APP.:	L.V. SOEST.
DATE:	14-08-92	DATE:	-	DATE:	-
DWG. No.		REV. LTR.		SHEET	
C-100733		0		1 OF 1	A4

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2-100733-2](#)