



1. CONNECTOR MATES WITH ANY 9 POSN PLUG IN AMPLIMITE SERIES.
2. MOLDED PARTS: FLAME RETARDANT 94V-0 RATED THERMOPLASTIC, BLACK.  
SHELL: STEEL PER ASTM A109  
CONTACTS: PHOSPHOR BRONZE PER QQ-B-750  
EYELETS: BRASS  
SCREWLOCKS: ZINC  
INSERTS: ZINC  
BOARDLOCKS: COPPER ALLOY
3. SHELL: .000100 MIN TIN  
CONTACTS: SEE TABLE  
EYELETS: TIN  
SCREWLOCKS: CLEAR CHROMATE  
BOARDLOCKS: TIN.  
INSERTS: CLEAR CHROMATE
4. GOLD FLASH FOR A DISTANCE OF .100 MIN FROM MATING END, .000100-.000200 TIN ON TERMINATION END, ALL OVER .000050 NICKEL ON ENTIRE CONTACT.
5. .000030 GOLD FOR A DISTANCE OF .100 MIN FROM MATING END, .000100-.000200 TIN ON TERMINATION END, ALL OVER .000050 NICKEL ON ENTIRE CONTACT.
6. SCREWLOCKS & INSERTS WILL WITHSTAND 4 IN LBS TORQUE & 20 LBS PULL OUT FORCE FROM MATING FACE SIDE.
7. DIMENSION APPLIES TO CENTER LINE OF CONTACTS.

-	FEMALE SCREWLOCKS	(5)	5747844-6																												
-	FEMALE SCREWLOCKS	(4)	5747844-5																												
TRAY	THREADED INSERTS	(5)	5747844-4																												
-	THREADED INSERTS	(4)	5747844-3																												
-	.125 DIA HOLES	(5)	5747844-2																												
PACKAGING	MOUNTING HARDWARE	CONTACT FINISH	PART NUMBER																												
THIS DRAWING IS A CONTROLLED DOCUMENT.		<table border="1"> <tr> <td>DIN</td> <td>L.VARELA - DOCK5</td> <td>18MAR205</td> </tr> <tr> <td>CHK</td> <td>S.BOLASH</td> <td>18MAR205</td> </tr> <tr> <td>APVD</td> <td>M.WALMSLEY</td> <td>18MAR205</td> </tr> </table>		DIN	L.VARELA - DOCK5	18MAR205	CHK	S.BOLASH	18MAR205	APVD	M.WALMSLEY	18MAR205																			
DIN	L.VARELA - DOCK5	18MAR205																													
CHK	S.BOLASH	18MAR205																													
APVD	M.WALMSLEY	18MAR205																													
<table border="1"> <tr> <th>DIMENSIONS:</th> <th>TOLERANCES UNLESS OTHERWISE SPECIFIED:</th> </tr> <tr> <td>0 PLC</td> <td>± -</td> </tr> <tr> <td>1 PLC</td> <td>± -</td> </tr> <tr> <td>2 PLC</td> <td>± -</td> </tr> <tr> <td>3 PLC</td> <td>± .005</td> </tr> <tr> <td>4 PLC</td> <td>± -</td> </tr> <tr> <td>ANGLES</td> <td>± - °</td> </tr> </table>		DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:	0 PLC	± -	1 PLC	± -	2 PLC	± -	3 PLC	± .005	4 PLC	± -	ANGLES	± - °	<table border="1"> <tr> <td>NAME</td> <td>RECEPTACLE ASSEMBLY, SIZE 1, RIGHT ANGLE, .318 SERIES, FRONT METAL SHELL, .026 DIA POSTS, BOARDLOCKS, AMPLIMITE HD-20</td> </tr> <tr> <td>PRODUCT SPEC</td> <td>108-40025</td> </tr> <tr> <td>APPLICATION SPEC</td> <td>114-40010</td> </tr> <tr> <td>SIZE</td> <td>A1</td> </tr> <tr> <td>CAGE CODE</td> <td>00779</td> </tr> <tr> <td>DRAWING NO</td> <td>5747844</td> </tr> <tr> <td>RESTRICTED TO</td> <td></td> </tr> </table>		NAME	RECEPTACLE ASSEMBLY, SIZE 1, RIGHT ANGLE, .318 SERIES, FRONT METAL SHELL, .026 DIA POSTS, BOARDLOCKS, AMPLIMITE HD-20	PRODUCT SPEC	108-40025	APPLICATION SPEC	114-40010	SIZE	A1	CAGE CODE	00779	DRAWING NO	5747844	RESTRICTED TO	
DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:																														
0 PLC	± -																														
1 PLC	± -																														
2 PLC	± -																														
3 PLC	± .005																														
4 PLC	± -																														
ANGLES	± - °																														
NAME	RECEPTACLE ASSEMBLY, SIZE 1, RIGHT ANGLE, .318 SERIES, FRONT METAL SHELL, .026 DIA POSTS, BOARDLOCKS, AMPLIMITE HD-20																														
PRODUCT SPEC	108-40025																														
APPLICATION SPEC	114-40010																														
SIZE	A1																														
CAGE CODE	00779																														
DRAWING NO	5747844																														
RESTRICTED TO																															
MATERIAL	FINISH	WEIGHT	CUSTOMER DRAWING																												
(6)	(6)		SCALE 4:1 SHEET 1 OF 1 REV P																												

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[5747844-2](#)