





	Bestell-Nummer /PART NO versilbert /silverplated	ϕ	Leiterquerschnitt wire gauge mm ² AWG		Abisolierlänge der Litze stripping length
Stiftkontakt male contact	09 35 000 6103	1,15	0,5	20	6,0
	09 35 000 6104	1,3	0,75	18	
	09 35 000 6105	1,45	1,0	18	
	09 35 000 6106	1,75	1,5	16	
	09 35 000 6107	2,25	2,5	14	
Buchsenkontakt female contact	09 35 000 6203	1,15	0,5	20	6,0
	09 35 000 6204	1,3	0,75	18	
	09 35 000 6205	1,45	1,0	18	
	09 35 000 6206	1,75	1,5	16	
	09 35 000 6207	2,25	2,5	14	



Techn. Character.

Nicht tolerierte Maß/Free size tolerances

	Dat.	Name	Maßstab/Scale
Detail.	10.11.10	ML	2:1
Insp.		Be	
Stand.			

Han P Kontakte gedreht 16A
Han P contacts turned 16A

A		
Mod.	Dat.	Name

HARTING Electric GmbH & Co. KG
D-32339 Espelkamp



TB 09 35 000 6...
Sub. f. TB 09 35 000 6... v. 28.03.07

Blatt/ page

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HARTING:](#)

[09350006107](#)