
UNCONTROLLED DOCUMENT


(\mathbf{X})	DART NUMBER		
	LDD-C406NI	В	
REV	E.C.N. NUMBER AND REVISION COMMENTS	DATE	
Α	E.C.N. #10BRDR、& REDRAWN,	2-12-99	
В	E.C.N. #11148.	4.30.07	



20.10 [0.791] -

2.50 [0.098] (7 PLS.)

└---- 17,50 [0,689] ----



CHARACTER DETAIL

В

G


DIG.1

ELECTRO-OPTICAL CHARACTERISTICS TA=25'C If=10mA							
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND		
PEAK WAVELENGTH		660 (RED)		nm			
FORWARD VOLTAGE		1.7	2.3	Vf			
REVERSE VOLTAGE	4.0			Vr	lr=100μΑ		
AXIAL INTENSITY		6300		μcd	lf=10mA		
EMITTED COLOR;	RED						
FACE COLOR:	GRAY						
SEGMENT COLOR:	MILKY	WHITE DIFFUSED)				

LIMITS OF SAFE OPERATION AT 25'C PER CHIP

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	- 1.2	m₩/°C
OPERATING, STORAGE TEMP.	- 40 TO + 85	°C
SOLDERING TEMP.	+ 260	. С
2.0mm FROM BODY		3 SEC. MAX
* 1 /10.0		

* t<10µS



			 15 13 1]]]] 3 2 14 16	10 12 B 6 7	11 9		
VINLESS OTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +0.000 -0.000								
REV.	PART NUMBER	<u>confidential information</u> The information contained in this document is the property of	I ITA		E. HELEN ROA ATINE. IL 600	4D 67-6976	A	
В	LDD-C406NI	LUMEX NG. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUNEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCUSSER AND DISSEMINATION TO ALL THRO PARTIES.			NE: +1.847.35 WEB: www.lume WEB: www.lume	9,2790 ex.com		
66	0.40" SEVEN SEGMENT, DUAL DIGIT DISPLAY, 50nm RED CHIPS, GRAY FACE WITH WHITE SEGMENTS, COMMON CATHODE, NO CHIPS IN DECIMALS.	Reliability nate our namy years of experience data accumulation indicate that solder heat is a major cause of early and future failure. Please pay attention to your soldering process.	DRAWN BY:		APPROVED BY:	DATE: 1. PAGE: 1	.16.97 OF 1 N/A	

8*

DIG.2

10.20 [0.402]

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: LDD-C406NI