

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

FT

0

P

LTR

DESCRIPTION

DATE

DWN

APVD

B2

REVISED PER ECO-12-015027

21AUG2012

KH

MB

POLARIZATION KEY SLOT  
CAVITY FOR M2.5 FIXING SCREW

284539-3 AS SHOWN

1

MATERIALS AND FINISH  
HOUSING : PA 6.6, UL 94-V0, COLOR GREEN  
TERMINAL : PHOSPHOR BRONZE, TIN PLATED  
SQUARE NUT-CuZn42 ALLOY

2

CONNECTOR ASSEMBLY INCLUDED 2 SQUARE NUTS  
LOADED IN CAVITY.

3

SUITABLE FOR 1.6-2.4 mm. PC BOARD THICKNESS.

4

NOT CUMULATIVE TOLERANCE.

5

ADDITIONAL SQUARE NUTS INCLUDED.

6

PACKAGED IN A BAG.

77.0	23	2-284539-3
73.5	22	2-284539-2
70.0	21	2-284539-1
66.5	20	2-284539-0
63.0	19	1-284539-9
59.5	18	1-284539-8
56.0	17	1-284539-7
52.5	16	1-284539-6
49.0	15	1-284539-5
45.5	14	1-284539-4
42.0	13	1-284539-3
38.5	12	1-284539-2
35.0	11	1-284539-1
31.5	10	1-284539-0
28.0	9	284539-9
24.5	8	284539-8
21.0	7	284539-7
17.5	6	284539-6
14.0	5	284539-5
10.5	4	284539-4
7.0	3	284539-3
3.5	2	284539-2
DIM A	NO OF POS	PART NUMBER

RECOMMENDED PC BOARD LAYOUT

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS  
OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±.3
2 PLC	±.25
3 PLC	±-
4 PLC	±-
ANGLES	±2

MATERIAL

FINISH

DWN 07FEB2002

E. ZANOLINI

CHK 07FEB2002

E. ZANOLINI

APVD 07FEB2002

D. BIEVENOUR

PRODUCT SPEC

108-20166

APPLICATION SPEC

114-20079

WEIGHT

-

Customer Drawing

TE Connectivity

NAME  
TERMINAL BLOCK, HEADER ASSEMBLY  
90 DEG 3.5mm PITCH  
WITH THREADED FLANGE

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C-284539

SCALE

3:1

SHEET

OF

1

REV

B2

1470-19 (3/11)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[284539-8](#)