


Female Disconnects – Non-Insulated Butted Seam Flag




Product Number [†]	UPC (054007-)	Wire Range (AWG)	Mates with Male Tab Width(W') x Thickness	L	Barrel Length	Barrel I.D.	Terminals per:	
							Carton	Case
MU18-187DF/FLAGX*	22138	22-18	0.187 x 0.020	0.46	0.20	0.075	100	500
MU18-187DF/FLAGK*	01302	22-18	0.187 x 0.020	0.46	0.20	0.075	—	1000
MU18-250DF/FLAGX	22146	22-18	0.250 x 0.032	0.50	0.25	0.075	100	500
MU18-250DF/FLAGK	01303	22-18	0.250 x 0.032	0.50	0.25	0.075	—	1000
MU14-187DF/FLAGX*	22948	16-14	0.187 x 0.020	0.47	0.20	0.095	100	500
MU14-187DF/FLAGK*	01778	16-14	0.187 x 0.020	0.47	0.20	0.095	—	1000
MU14-250DF/FLAGX	22955	16-14	0.250 x 0.032	0.51	0.26	0.095	100	500
MU14-250DF/FLAGK	01779	16-14	0.250 x 0.032	0.51	0.26	0.095	—	1000
MU10-250DF/FLAGK	02245	12-10	0.250 x 0.032	0.63	0.25	0.175	—	500


* Not ULListed or CSACertified




MU18-187DF/FLAG




MU18-250DF/FLAG



MU14-187DF/FLAG



MU14-250DF/FLAG



MU10-250DF/FLAG

Wire Range
Suggested Mate

22-18
0.187 Male Tab

22-18
0.250 Male Tab

16-14
0.187 Male Tab

16-14
0.250 Male Tab

12-10
0.250 Male Tab

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

3M:

[MU14-187DF/FLAGK](#)