

XUYFVPTD61

FV PTD 61 FIBRE VERRE REFLEXION DIRECTE 60CM GAINÉ HAUTE TEMP EMBOUT DROIT

Electrical

| | |
|------------------------|-----------------------|
| Electronic sensor type | Photo-electric sensor |
|------------------------|-----------------------|

Environment

| | |
|---------------------------------------|--------------|
| Ambient air temperature for operation | -25...200 °C |
|---------------------------------------|--------------|

Functional

| | |
|-------------------------------|------|
| [Sn] nominal sensing distance | 80 m |
|-------------------------------|------|

Installation

| | |
|---------------|----------|
| Head mounting | M4 x 0.7 |
|---------------|----------|

Physical characteristics

| | |
|------------------------|--------------------------|
| Minimum bending radius | 30 mm |
| Optic fiber length | 0.6 m |
| Optic fiber material | 50 µ glass |
| Product weight | 0.052 kg |
| Sheath material | Flexible stainless steel |

Product identification

| | |
|------------------|--|
| End fitting type | Straight in nickel plated brass M4 x 0.7 |
| Range of product | Osiris |
| Sensor design | Fiber design |
| Sensor name | XUY |
| Sheath type | High temperature |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[XUYFVPTD61](#)