

DESCRIPTION: 2mm HEADER STRIP STRAIGHT

"L" = NO. OF PINS/ROW X .079 - .079

2663 YY 01RP2

SERIES _____
 2663 = SINGLE ROW

POSITIONS _____
 SINGLE- INCRMENTS OF 1
 (01-36)

TYPE _____
 01 = STRAIGHT

PLATING _____
 P2 = GOLD FLASH ENTIRE CONTACT



MATERIALS:
 HOUSING: NYLON 6T - UL 94V-0
 COLOR: BLACK
 CONTACTS: COPPER ALLOY
 PLATING: GOLD FLASH ENTIRE CONTACT
 RoHS COMPLIANT

CURRENT RATING: 1 AMP
 INSUALTOR RESISTANCE: 5000 MEGOHMS MIN.
 DIELECTRIC WITHSTANDING: 500V AC
 OPERATING TEMP: -40°C TO +105°C
 MAX PROCESSING TEMP: 260°C FOR
 10 SECONDS

	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.		DRAWN: PAM JENKINS	DATE: 1-27-06
			CHECKED:	DATE:
NorComp		SCALE:	SHEET 1 OF 1	REV 2
		DWG NO. 2663YY01RP2		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

NorComp:

[26630101RP2](#) [26630201RP2](#) [26630301RP2](#) [26630401RP2](#) [26630501RP2](#) [26630601RP2](#) [26630701RP2](#)
[26630801RP2](#) [26630901RP2](#) [26631001RP2](#) [26631201RP2](#) [26631501RP2](#) [26631601RP2](#) [26632001RP2](#)
[26632401RP2](#) [26632501RP2](#) [26632601RP2](#) [26633601RP2](#) [26631101RP2](#) [26631401RP2](#) [26632701RP2](#)