



Product availability: Stock - Normally stocked in distribution facility



Main

Commercial Status	Commercialised
Range of product	OsiSense XX
Sensor type	Ultrasonic sensor
Series name	General purpose
Sensor name	XX7
Sensor design	Flat form 18 x 33 x 60 + cylindrical M18
Detection system	Diffuse
[Sn] nominal sensing distance	1.64 ft (0.5 m) adjustable with remote teach pushbutton
Material	Plastic
Type of output signal	Discrete
Discrete output function	1 NO
Wiring technique	3-wire
Discrete output type	PNP
[Us] rated supply voltage	12...24 V DC with reverse polarity protection
Electrical connection	Male connector M12 4 pins
[Sd] sensing range	0.17...1.67 ft (0.051...0.508 m)
Beam angle	12 °
IP degree of protection	IP67 conforming to IEC 60529

Complementary

Enclosure material	Valox
Front material	Epoxy
Supply voltage limits	10...28 V DC
[Sa] assured operating distance	0.17...1.67 ft (0.051...0.508 m) (teach mode)
Maximum differential travel	0.1 in (2.5 mm)
Blind zone	0...2.01 in (0...51 mm)
Transmission frequency	300 kHz
Repeat accuracy	1.27 %
Minimum size of detected object	Flat bar 1 mm wide up to 150 mm sensing distance Cylinder diameter 2.5 mm up to 150 mm sensing distance
Status LED	1 LED (yellow) for output state 1 LED (green) for supply on
Current consumption	40 mA
Maximum switching current	100 mA
Voltage drop	< 1 V
Switching frequency	<= 40 Hz
Delay first up	100 ms
Delay response	10 ms
Delay recovery	10 ms
Marking	CE
Height	1.73 in (44 mm)
Width	0.71 in (18 mm)
Depth	2.36 in (60 mm)
Product weight	0.13 lb(US) (0.06 kg)

Environment

Standards	IEC 60947-5-2
Ambient air temperature for operation	-4...149 °F (-20...65 °C)
Ambient air temperature for storage	-40...176 °F (-40...80 °C)
Vibration resistance	+/-1 mm conforming to IEC 60068-2-6 10...55 Hz
Shock resistance	30 gn in all 3 axes for 11 ms conforming to IEC 60068-2-27
Resistance to electrostatic discharge	8 kV level 4 conforming to IEC 61000-4-2
Resistance to electromagnetic fields	9.14 V/yd (10 V/m) level 3 conforming to IEC 61000-4-3
Resistance to fast transients	1 kV level 3 conforming to IEC 61000-4-4

Ordering and shipping details

Category	22490 - SENSORS-ULTRASONIC (XX5,6)
Discount Schedule	DS2
GTIN	00785901684176
Nbr. of units in pkg.	1
Package weight(Lbs)	0.14
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 1140 - Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold - go to CaP for more details
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Available Download End Of Life Manual

Contractual warranty

Period	18 months
--------	-----------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric:

[XX7V1A1PAM12](#) [XX930A2A1M12](#) [XX512A260KAM12L](#) [XX230A30KA00M12](#) [XX930A2B4050L3](#)
[XX512AH20KBM12](#) [XX318AU081KAM12](#) [XX2V1A1PKM12J14](#) [XX8D1A1PBM12](#) [XX930A1A2M12J20](#)
[XX9V3A1D2M12J14](#) [XX630AS1000](#) [XX6V3A1NAM12JZZ](#) [XX512AH20KBM8](#) [XX930A3A1050M12](#)
[XX930A1A2030MAT](#) [XX9V3A1F6M12](#) [XX7V1A1PAM12D](#) [XX630A3KA000L3](#) [XX230A10KA00M12](#)
[XX230A30KA02L3](#) [XX8D1A1PAM12J12](#) [XX230A11KA00M12](#) [XX518A3NAL02](#) [XX930A2A2M12](#) [XX512AR12KBM8](#)
[XX7V1A1PAM12J13](#) [XX518A3PAM12J45](#) [XX230A11KA00M42](#) [XX218A3PAM12Z81](#) [XX218A100AVAJ40](#)
[XX930B1A1000M12](#) [XX930A2A1000M12](#) [XX230A21KA00M12](#) [XX630A2KA000M12](#) [XX7K1AT08K21MTE](#)
[XX230A22PC00M12](#) [XX8D1A1NBM12](#) [XX512AC36KAM218](#) [XX930A2A2030L3](#) [XX318AA08KAL3](#)
[XX7K1A780KBM12](#) [XX218A3NAM12Z81](#) [XX7F1A260NAM12L](#) [XX930AEA1000L3](#) [XX9V3A1H3M12J91](#)
[XX930A3B1000M12](#) [XX930B1A2000M12](#) [XX930A2B4000MAD](#) [XX930A2A1030L3](#) [XX930A3A2050M12](#)
[XX930A3P4KM12](#) [XX518A164K16M12](#) [XX3K1AA081KAM12](#) [XX8D1A1PAM12J14](#) [XX630A1PC000M80](#)
[XX930S1001](#) [XX930A3A2150MTF](#) [XX518A3PAL02](#) [XX9V3A1D2M12JE2](#)