

## Specification Sheet

Part Number: 170-03026



Braided Sleeving, Split Wrap, 1.25" Dia, PET, Black, 25 ft/reel

**Article Number**

170-03026

**Type**

BSPSW1140

**Color**

Black (BK)

**Features & Benefits**

- Center-slit overlapping design allows quick and easy access to the wires and cables for future maintenance or inspection without disassembly.
- Flexible material allows it to easily wrap around a variety of component shapes and sizes, making it easier to use than slit-loom tubing or spiral-wrap materials.
- A unique weave pattern provides increased coverage and greater resistance to abrasion, dust and debris.
- Overlapping design enhances flexibility, allowing it to shift and bend without exposing wire and cables.

**Quantity Per**

reel

|                                       |  |
|---------------------------------------|--|
| <b>Product Description</b>            | A lateral split semi-rigid braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires. |
| <b>Short Description</b>              | Braided Sleeving, Split Wrap, 1.25" Dia, PET, Black, 25 ft/reel  |
| <b>Global Part Name</b>               | BSPSW1140-PET-BK   |
| <b>Length L (Imperial)</b>            | 25.0   |
| <b>Length L (Metric)</b>              | 7.62   |
| <b>Bundle Diameter Min (Imperial)</b> | 0.1  |
| <b>Bundle Diameter Min (Metric)</b>   | 2.54   |
| <b>Bundle Diameter Max (Imperial)</b> | 1.25   |
| <b>Bundle Diameter Max (Metric)</b>   | 31.8   |
| <b>Diameter D (imperial)</b>          | 0.25   |
| <b>Diameter D (metric)</b>            | 6.4  |
| <b>Nominal Diameter (Imperial)</b>    | 1.25   |
| <b>Nominal Diameter (Metric)</b>      | 31.8   |
| <b>Wall Thickness WT (Imperial)</b>   | 0.038  |

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| <b>Wall Thickness WT (Metric)</b>     | 0.97                              |
| <b>Material</b>                       | Polyester (PET)                   |
| <b>Material Shortcut</b>              | PET                               |
| <b>Flammability</b>                   | UL 94 V0                          |
| <b>Halogen free</b>                   | Yes                               |
| <b>Operating Temperature (Metric)</b> | -94°F to +257°F (-70°C to +125°C) |
| <b>Reach Complaint(Article 33)</b>    | Yes                               |
| <b>ROHS Complaint</b>                 | Yes                               |
| <b>UL Recognized (US)</b>             | Yes                               |
| <b>Package Quantity(Imperial)</b>     | 25                                |
| <b>Package Quantity (Metric)</b>      | 7.62                              |
| <b>Customs Number</b>                 | 5808100000                        |
| <b>Weight (Metric)</b>                | 0.27                              |
| <b>Weight (Imperial)</b>              | 0.6                               |

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)