

XUX9APBNT16

photo-electric sensor - XUX - polarised - Sn
11m - 12..24VDC - terminals



Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Commercial Status	Commercialised
Range of product	OsiSense XU
Series name	General purpose single mode
Electronic sensor type	Photo-electric sensor
Sensor name	XUX
Sensor design	Compact 92 x 71
Detection system	Polarised reflex
Material	Plastic
Type of output signal	Discrete
Supply circuit type	DC
Wiring technique	3-wire
Discrete output function	1 NC
Electrical connection	Screw-clamp terminals, 1 x 1.5 mm ² or 1 x 0.75 mm ² with adaptor
Product specific application	-
Emission	Red polarised reflex
[Sn] nominal sensing distance	36.09 ft (11 m) polarised reflex need reflector XUZC50

Complementary

Enclosure material	PBT
Lens material	PMMA
Maximum sensing distance	49.21 ft (15 m) polarised reflex
Output type	Solid state
Cable entry	1 entry for M16 x 1.5 cable gland, cable outer diameter: 0.28...0.39 in (7...10 mm)
Status LED	1 LED (green) for supply 1 LED (yellow) for output state
[Us] rated supply voltage	12...24 V DC
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)
Switching frequency	<= 250 Hz
Voltage drop	<= 1.5 V (closed state)
Current consumption	<= 35 mA (no-load)
Delay first up	< 15 ms
Delay response	< 2 ms
Delay recovery	< 2 ms
Setting-up	Sensitivity adjustment
Depth	3.03 in (77 mm)
Height	3.62 in (92 mm)
Width	1.22 in (31 mm)
Product weight	0.44 lb(US) (0.2 kg)

Environment

Product certifications	CE CSA UL
Ambient air temperature for operation	-13...131 °F (-25...55 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)
Vibration resistance	7 gn, amplitude = +/- 1.5 mm (f = 10...55 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 11 ms) conforming to IEC 60068-2-27
IP degree of protection	IP65 double insulation conforming to IEC 60529 IP67 double insulation conforming to IEC 60529

Ordering and shipping details

Category	22481 - SENSORS, PHOTOELECTRIC
Discount Schedule	DS2
GTIN	00785901567554
Nbr. of units in pkg.	1
Package weight(Lbs)	0.42
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	FR

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 1136 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Available Download End Of Life Manual

Contractual warranty

Period	18 months
--------	-----------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric:

[XUX0AKSAT16T](#) [XUX0ARCTT16T](#) [XUX0AKSAM12T](#) [XUX1ARCNT16](#) [XUX9ARCNT16](#) [XUX5ARCNT16](#)
[XUX2ANANT16R](#) [XUX1ANANM12](#) [XUX5APANT16](#) [XUX5APBNM12](#) [XUX9ANBNM12](#) [XUX2APBNT16R](#)
[XUX9APANM12](#) [XUX5ANANM12](#) [XUX1ANBNM12](#) [XUX1APBNT16](#) [XUX2ANBNT16R](#) [XUX2APANT16R](#)
[XUX2APANM12R](#) [XUX1ANBNT16](#) [XUX1ANANT16](#) [XUX1APANM12](#) [XUX9ANANM12](#) [XUX2ANANM12R](#)
[XUX5ANBNT16](#) [XUX1APANT16](#) [XUX5APANM12](#) [XUX2APBNM12R](#) [XUX2ANBNM12R](#) [XUX9APBNM12](#)
[XUX5ANBNM12](#) [XUX5APBNT16](#) [XUX9ANANT16](#) [XUX9APANT16](#) [XUX9ANBNT16](#) [XUX9APBNT16](#) [XUX5ANANT16](#)
[XUX2ARCNT16R](#) [XUX1APBNM12](#)