



Product: [83046](#)

Lead Wire, #26 Str SPC, TFE Ins, AWM 1371

[Request Sample](#)

Product Description

High Temp Plastic Lead Wire, 26AWG (7x34) Silver Plated Copper, TFE Insulation, AWM 1371 105C TYPE ET MIL-W-16878/6 250V 200C

Technical Specifications

Product Overview

| | |
|------------------------|--|
| Suitable Applications: | high temperature, inter-connection circuits, internal wiring of computer and electronic equipments, (Type ET) MIL-W-16878/6 applications |
|------------------------|--|

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material | No. of Conductors |
|-----|-----------|----------------------|-------------------|
| 26 | 7x34 | SC - Silvered Copper | 1 |

Conductor Count: 1

Insulation

| Material | Nominal Diameter | Nominal Wall Thickness |
|--------------------------------|------------------|------------------------|
| PTFE - Polytetrafluoroethylene | 0.031 in | 0.006 in |

Electrical Characteristics

Current

| Max. Recommended Current [A] |
|--|
| Mil-Std-975M Table 3.16 (single wire): 2.5 A |

Voltage

| UL Voltage Rating |
|-------------------|
| 250 V RMS |

Temperature Range

| | |
|---------------------|-------|
| Non-UL Temp Rating: | 200°C |
| UL Temp Rating: | 105°C |

Mechanical Characteristics

| | |
|--------------------|----------------|
| Bulk Cable Weight: | 1.4 lbs/1000ft |
|--------------------|----------------|

Standards

| | |
|--------------------------|-------------------|
| UL AWM Style Compliance: | UL AWM Style 1371 |
| NEMA Compliance: | HP3 |
| Military Compliance: | MIL-W-16878/6 |

Applicable Environmental and Other Programs

| | |
|------------------------------------|-----|
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |

| | |
|---------------------------------------|-------------------------------|
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-04-01 |
| CA Prop 65: | Yes |
| MII Order #39 (China RoHS): | Yes |

Flammability, LSOH, Toxicity Testing

| | |
|--------------------|-----------|
| UL Flammability: | VW-1 |
| UL voltage rating: | 600 V RMS |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Part Number

Variants

| Item # | Color | Putup Type | Length | UPC |
|---------------|-------------|------------|----------|--------------|
| 83046 0101000 | Black | Reel | 1,000 ft | 612825354901 |
| 83046 0061000 | Blue, Light | Reel | 1,000 ft | 612825399674 |
| 83046 0011000 | Brown | Reel | 1,000 ft | |
| 83046 0031000 | Orange | Reel | 1,000 ft | |
| 83046 0021000 | Red | Reel | 1,000 ft | 612825354918 |
| 83046 0071000 | Violet | Reel | 1,000 ft | |
| 83046 009100 | White | Reel | 100 ft | |
| 83046 0091000 | White | Reel | 1,000 ft | |
| 83046 0041000 | Yellow | Reel | 1,000 ft | |

| | |
|-----------|---|
| Footnote: | E - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'. |
| Footnote: | S - STRIPING ADDERS FOR TYPES E AND EE: 1, 2, 3 STRIPES. MINIMUM ORDER 10,000' PER STRIPE COMBINATION. (SEE STRIPING ADDER TABLE) |

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.295 Revision Date: 07-26-2020 |
|----------------------|--|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.