



Product: [83552](#)

Electronic, 2 C #22 Str TC, FEP Ins, OS+TC Brd, FEP Jkt, CMP

[Request Sample](#)

Product Description

High Temperature Electronic, 2 Conductor 22AWG (7x30) Tinned Copper, FEP Insulation, Overall Beldfoil®+Tinned Copper Braid(85%) Shield, FEP Outer Jacket, CMP

Technical Specifications

Product Overview

| | |
|------------------------|---|
| Suitable Applications: | extreme high/low temperature environments; chemical resistant; outdoor and burial applications; low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); line level audio; voice communications; panel wiring |
|------------------------|---|

Physical Characteristics (Overall)

Conductor

| Element | AWG | Stranding | Material | No. of Conductors |
|--------------|-----|-----------|--------------------|-------------------|
| Conductor(s) | 22 | 7x30 | TC - Tinned Copper | 2 |

| | |
|------------------------|---|
| Conductor Count: | 2 |
| Total Number of Pairs: | 1 |

Insulation

| Element | Material | Nominal Wall Thickness |
|--------------|--------------------------------------|------------------------|
| Conductor(s) | FEP - Fluorinated Ethylene Propylene | 0.0065 in |

Color Chart

| Number | Color |
|--------|-------|
| 1 | Black |
| 2 | White |

Outer Shield Material

| Type | Layer | Material | Material Trade Name | Coverage [%] |
|-------|-------|--------------------|---------------------|--------------|
| Tape | 1 | Alum / Poly | Beldfoil® | 100 % |
| Braid | 2 | TC - Tinned Copper | | 85 % |

Outer Jacket Material

| Material | Nominal Diameter | Nominal Wall Thickness |
|--------------------------------------|------------------|------------------------|
| FEP - Fluorinated Ethylene Propylene | 0.141 in | 0.014 in |

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Nominal Outer Shield DCR |
|-----------------------|--------------------------|
| 14.5 Ohm/1000ft | 7.5 Ohm/1000ft |

Capacitance

| Nom. Capacitance Conductor to Conductor | Nom. Capacitance Conductor to Other Conductor to Shield |
|---|---|
| 35 pF/ft | 63 pF/ft |

Current

| |
|-------------------------------------|
| Max. Recommended Current [A] |
| 2.75 Amps per conductor @ 25°C |

Voltage

| |
|--------------------------|
| UL Voltage Rating |
| 300 V RMS |

Temperature Range

| | |
|-----------------------|-----------------|
| Operating Temp Range: | -70°C To +200°C |
|-----------------------|-----------------|

Mechanical Characteristics

| | |
|----------------------------------|---------------|
| Bulk Cable Weight: | 16 lbs/1000ft |
| Max Recommended Pulling Tension: | 19 lbs |
| Min Bend Radius/Minor Axis: | 1.5 in |

Standards

| | |
|--------------------------|-----|
| NEC Articles: | 800 |
| NEC/(UL) Specification: | CMP |
| CEC/C(UL) Specification: | CMP |

Applicable Environmental and Other Programs

| | |
|---------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-01-01 |
| CA Prop 65: | Yes |
| MII Order #39 (China RoHS): | Yes |

Flammability, LSOH, Toxicity Testing

| | |
|--------------------|-----------|
| UL Flammability: | NFPA 262 |
| CSA Flammability: | FT6 |
| UL voltage rating: | 300 V RMS |

Plenum/Non-Plenum

| | |
|---------------|-----|
| Plenum (Y/N): | Yes |
|---------------|-----|

Part Number

Variants

| Item # | Color | Putup Type | Length | UPC |
|---------------|-------|------------|----------|--------------|
| 83552 002500 | Red | Reel | 500 ft | 612825204909 |
| 83552 0021000 | Red | Reel | 1,000 ft | 612825204893 |

| | |
|-----------|------------------------|
| Footnote: | C - CRATE REEL PUT-UP. |
|-----------|------------------------|

Product Notes

| | |
|--------|--|
| Notes: | Plenum Cables, except for Flamarrrest [®] jacket, are suitable for Outdoor and Direct Burial application. |
|--------|--|

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.288 Revision Date: 05-05-2020 |
|----------------------|--|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Belden Wire & Cable:](#)

[83552 002500](#) [83552 0021000](#)