



**NOTE(S):**

1. MATERIAL: POLYESTER (PBT)  
COLOR: BLACK  
UL FLAMMABILITY RATING: UL94 V-0
2. USE WITH MOLEX XRC RECEPTACLE CONNECTORS  
SERIES 84506 AND 84511.
3. RECOMMENDED TORQUE: 65-75 IN-LB [7.3-8.5 N-M]
4. MATERIAL IS ROHS COMPLIANT.

LAST INSPECTION NO.: ④

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION											
<b>QUALITY SYMBOLS</b> = 0 = 0 = 0 = 0 = 0 = 0 = 0 = 0 = 0	EC NO: 122085 DRWN: CRAODOREMS CHK'D: SMCGREEVY REV APPR: JDWALLACE	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION UNITS	SCALE						
				IN[MM]	2:1						
		MM	INCH	DRWN BY	DATE						
				4 PLACES ±	±	WLEUNG	2008/12/16	PANEL HEX NUT, PIN OR SOCKET RECEPTACLE 24 SHELL			
				3 PLACES ±	± 0.015	CHK'D BY	DATE				
				2 PLACES ± 0.38	±	WLEUNG	2008/12/16	PRODUCT CUSTOMER DRAWING			
				1 PLACES ±	±	APPR BY	DATE				
				0 PLACES ±	±	RDEROSS	2008/12/16	SERIES MATERIAL NUMBER CUSTOMER 84506 845060012 GENERAL MARKET			
				ANGULAR TOL ± 2.0		DRAWING SIZE	THIRD ANGLE PROJECTION				
				DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		<b>B</b>		DOCUMENT NUMBER DOC TYPE DOC PART SHEET NUMBER SD-84506-012 PSD 001 1 OF 1			