


Product data sheet

Characteristics

XZCP1440L2

pre-wired connectors XZ - elbowed female - M12 - 3 pins - cable PUR 2m

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Commercial Status	Commercialised
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Pre-wired connectors
Series name	General purpose
Electrical connection	Elbowed female connector M12, 3 pins
Collar material	Metal
Status LED	2 NPN LEDs
Cable length	6.56 ft (2 m)

Complementary

Cable connector fixing	Screw-on
Cable outer diameter	0.2 in (5.2 mm)
Cable composition	3 x 0.34 mm ²
Wire insulation material	PUR
[Ue] rated operational voltage	10...30 V DC
[In] rated current	4 A
Contact resistance	<= 5000 µOhm
Insulating resistance	>= 1 GΩ
Product weight	0.18 lb(US) (0.08 kg)

Environment

IP degree of protection	IP67
Ambient air temperature for operation	23...176 °F (-5...80 °C) (flexing) -40...176 °F (-40...80 °C) (static)
Ambient air temperature for storage	-40...176 °F (-40...80 °C)

Ordering and shipping details

Category	22483 - MACHINE CABLES
Discount Schedule	DS3
GTIN	00785901703433
Nbr. of units in pkg.	1
Package weight(Lbs)	0.22
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	PL

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0726 - Schneider Electric declaration of conformity

Contractual warranty

Period	18 months
--------	-----------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[XZCP1440L2](#)