

3

Δ

Jac REMISCRIS GP
RIGHT ANGLE BRACKET, ADAPTER COMB & TERMINAL SUPPORT PLATE – PLASTIC, BLACK. 21 SHELD – BR CHT NICKEL OVER COPPER PLATED DIE CASTING. 35 – HIGH STRENGTH COPPER ALLOY PLATED WITH EITHER .000030 WIN NON MATING SUFFACE000120 MIN TIN PLATE ON TAILS. ALL OVER 36 – HIGH STRENGTH COPPER ALLOY PLATED WITH EITHER .000030 WIN NON MATING SUFFACE000120 MIN TIN PLATE ON TAILS. ALL OVER 37 – PASSIVATED STAINLESS STEEL. 38 – PASSIVATED STAINLESS STEEL. 39 – PASSIVATED STAINLESS STEEL. 30 CENTER SPACING OF TERVINALS ARE COATED WITH LUBRICANT. 30 CENTER SPACING OF TERVINALS IS .085 NOMINAL. 31 IS VIEWED FROM MATING SIDE OF THE RECEPTACLE ASSEVBLY. 35 ASSEVBLED TO RECEPTACLE ASSEMBLY BEFORE SHIPMENT. 36 ASSEVBLED TO RECEPTACLE ASSEMBLY BEFORE SHIPMENT. 37 IS LOCATED IN THIS ROW FOR STANDARD ORIENTAION, SEE DETAIL A. 40 KKESS RANGE: .062 MAXINUM. 30 BRACKET RETAINS CONNECTOR IN .062 THICK PC BOARD WITHOUT 41 HARDWARE. 34LS DO NOT EXTEND BELOW COMB, THEN COMB SHALL BE PARTIALLY 30, BERACKET LOCATES CONNECTOR FLUSH WITH TOP OF PC BOARD AND 30 CONS BENEATH. 31 SHAPE OFFERS 180° OF SOLDERING SURFACE. 32 AREA OF GROUNDING BRACKET BELOW PC BOARD SHALL PASS 33 BUITY REQUIREMENTS IN ACCORDANCE WITH AMP SPECIFICATION 34 CONTACT OF SOLDERING SURFACE. 34 AREA OF GROUNDING BRACKET BELOW PC BOARD SHALL PASS 34 BUITY REQUIREMENTS IN ACCORDANCE WITH AMP SPECIFICATION 32, DISCO.ORATION, SCRATHES, SPOTS AND OTHER COSMETIC DEFICIENCIES 34 DISCO.ORATION, SCRATHES, SPOTS AND OTHER PCVIDING PARTS PASS
RIGHT ANGLE BRACKET, ADAPTER COMB & TERMINAL SUPPORT PLATE – PLASTIC, BLACK. 2LE SHIELD – BRGHT NICKEL OVER COPPER PLATED DIE CASTING, S – HIGH STRENGTH COPPER ALLOY PLATED WITH EITHER .000030 MIN IATE OR GOLD FLASH OVER PALLADIUM NICKEL PLATE, .0000330 MIN NMAING SURFACE030120 MIN TIN PLATE ON TAILS. ALL OVER MIN NICKEL UNDERPLATE OVER ENTIRE TERMINAL. BRACKET – TIN PLATED CARBON STEEL. 'S – PASSIVATED STAINLESS STEEL. TACT SURFACES OF THE TERMINALS ARE COATED WITH LUBRICANT. TIG CENTER SPACING OF TERMINALS ARE COATED WITH LUBRICANT. IG CENTER SPACING OF TERMINALS IS .085 NOMINAL. 'NISIONS ARE MAX MUM UNLESS OTHERWISE SPECIFIED. '' IS VIEWED FROM MATING SIDE OF THE RECEPTACLE ASSEMBLY. S ASSEMBLED TO RECEPTACLE ASSEMBLY BEFORE SHIPMENT. . 1 IS LOCATED IN THIS ROW FOR STANDARD ORIENTAION, SEE DETAIL A. HICKNESS RANGE: .062 MAXIMUM. NG BRACKET RETAINS CONNECTOR IN .062 THICK PC BOARD WITHOUT AL HARDWARE. VALS DO NOT EXTEND BELOW COMB, THEN COM3 SHALL BE PARTIALLY D, BEFORE INSERTING CONNECTOR FLUSH WITH TOP OF PC BOARD AND .0CKS BENEATH. CAL SHAPE OFFERS 180' OF SOLDERING SURFACE. AREA OF GROUNDING BRACKET BELOW PC BOARD SHALL PASS BLITY REDUIREMENTS IN ACCORDANCE WITH AMP SPECIFICATION 2, DISCOLORATION, SCRATHES, SPOTS AND OTHER COSMETIC DEFICIENCIES OF BARREL PLATING PROCESS ARE ACCEPTABLE PROVIDING PARTS PASS
PLASTIC, BLACK. CLE SHIELD - BRIGHT NICKEL OVER COPPER PLATED DIE CASTING. S - HIGH STRENGTH COPPER ALLOY PLATED WITH EITHER .000030 MIN LATE OR GOLD FLASH OVER PALLADIUM NICKEL PLATE, .000030 MIN IN MATING SURFACE000120 MIN TIN PLATE ON TAILS. ALL OVER MIN NICKEL UNDERPLATE OVER ENTIRE TERMINAL. BRACKET - TIN PLATED CARBON STEEL. 'S - PASSIVATED STAINLESS STEEL. TACT SURFACES OF THE TERMINALS ARE COATED WITH LUBRICANT. TO CENTER SPACING OF TERMINALS IS .085 NOMINAL. NSIONS ARE MAXIMUM UNLESS OTHERWISE SPECIFIED. '' IS VIEWED FROM MATING SIDE OF THE RECEPTACLE ASSEMBLY. S ASSEMBLED TO RECEPTACLE ASSEMBLY BEFORE SHIPMENT. 1 IS LOCATED IN THIS ROW FOR STANDARD ORIENTAION, SEE DETAIL A. HICKNESS RANGE: .062 MAXIMUM. NG BRACKET RETAINS CONNECTOR IN .062 THICK PC BOARD WITHOUT AL HARDWARE. MALS DO NOT EXTEND BELOW COMB, THEN COMB SHALL BE PARTIALLY D, BEFORE INSERTING CONNECTOR INTO THE PC BOARD. NG BRACKET LOCATES CONNECTOR FLUSH WITH TOP OF PC BOARD AND .0CKS BENEATH. CAL SHAPE OFFERS 180° OF SOLDERING SURFACE. AREA OF GROUNDING BRACKET BELOW PC BOARD SHALL PASS BLITY REQUIREMENTS IN ACCORDANCE WITH AMP SPECIFICION 2, DISCOLORATION, SCRATHES, SPOTS AND OTHER COSMETIC DEFICIENCIES OF BARREL PLATING PROCESS ARE ACCEPTABLE PROVIDING PARTS PASS
PLASTIC, BLACK. CLE SHIELD - BRIGHT NICKEL OVER COPPER PLATED DIE CASTING. S - HIGH STRENGTH COPPER ALLOY PLATED WITH EITHER .000030 MIN LATE OR GOLD FLASH OVER PALLADIUM NICKEL PLATE, .000030 MIN IN MATING SURFACE000120 MIN TIN PLATE ON TAILS. ALL OVER MIN NICKEL UNDERPLATE OVER ENTIRE TERMINAL. BRACKET - TIN PLATED CARBON STEEL. 'S - PASSIVATED STAINLESS STEEL. TACT SURFACES OF THE TERMINALS ARE COATED WITH LUBRICANT. TO CENTER SPACING OF TERMINALS IS .085 NOMINAL. NSIONS ARE MAXIMUM UNLESS OTHERWISE SPECIFIED. '' IS VIEWED FROM MATING SIDE OF THE RECEPTACLE ASSEMBLY. S ASSEMBLED TO RECEPTACLE ASSEMBLY BEFORE SHIPMENT. 1 IS LOCATED IN THIS ROW FOR STANDARD ORIENTAION, SEE DETAIL A. HICKNESS RANGE: .062 MAXIMUM. NG BRACKET RETAINS CONNECTOR IN .062 THICK PC BOARD WITHOUT AL HARDWARE. MALS DO NOT EXTEND BELOW COMB, THEN COMB SHALL BE PARTIALLY D, BEFORE INSERTING CONNECTOR INTO THE PC BOARD. NG BRACKET LOCATES CONNECTOR FLUSH WITH TOP OF PC BOARD AND .0CKS BENEATH. CAL SHAPE OFFERS 180° OF SOLDERING SURFACE. AREA OF GROUNDING BRACKET BELOW PC BOARD SHALL PASS BLITY REQUIREMENTS IN ACCORDANCE WITH AMP SPECIFICION 2, DISCOLORATION, SCRATHES, SPOTS AND OTHER COSMETIC DEFICIENCIES OF BARREL PLATING PROCESS ARE ACCEPTABLE PROVIDING PARTS PASS
TACT SURFACES OF THE TERMINALS ARE COATED WITH LUBRICANT. TO CENTER SPACING OF TERMINALS IS .085 NOMINAL. INSIONS ARE MAXIMUM UNLESS OTHERWISE SPECIFIED. A" IS VIEWED FROM MATING SIDE OF THE RECEPTACLE ASSEMBLY. IS ASSEMBLED TO RECEPTACLE ASSEMBLY BEFORE SHIPMENT. . 1 IS LOCATED IN THIS ROW FOR STANDARD ORIENTAION, SEE DETAIL A. HICKNESS RANGE: .062 MAXIMUM. NG BRACKET RETAINS CONNECTOR IN .062 THICK PC BOARD WITHOUT AL HARDWARE. NALS DO NOT EXTEND BELOW COMB, THEN COMB SHALL BE PARTIALLY ID, BEFORE INSERTING CONNECTOR INTO THE PC BOARD. NG BRACKET LOCATES CONNECTOR FLUSH WITH TOP OF PC BOARD AND LOCKS BENEATH. CAL SHAPE OFFERS 180° OF SOLDERING SURFACE. AREA OF GROUNDING BRACKET BELOW PC BOARD SHALL PASS BLITY REQUIREMENTS IN ACCORDANCE WITH AMP SPECIFICATION .2, DISCOLORATION, SCRATHES, SPOTS AND OTHER COSMETIC DEFICIENCIES OF BARREL PLATING PROCESS ARE ACCEPTABLE PROVIDING PARTS PASS
NSIONS ARE MAXIMUM UNLESS OTHERWISE SPECIFIED. " IS VIEWED FROM MATING SIDE OF THE RECEPTACLE ASSEMBLY. S ASSEMBLED TO RECEPTACLE ASSEMBLY BEFORE SHIPMENT. 1 IS LOCATED IN THIS ROW FOR STANDARD ORIENTAION, SEE DETAIL A. HICKNESS RANGE: .062 MAXIMUM. NG BRACKET RETAINS CONNECTOR IN .062 THICK PC BOARD WITHOUT AL HARDWARE. WALS DO NOT EXTEND BELOW COMB, THEN COMB SHALL BE PARTIALLY D, BEFORE INSERTING CONNECTOR INTO THE PC BOARD. NG BRACKET LOCATES CONNECTOR FLUSH WITH TOP OF PC BOARD AND LOCKS BENEATH. CAL SHAPE OFFERS 180° OF SOLDERING SURFACE. AREA OF GROUNDING BRACKET BELOW PC BOARD SHALL PASS BLITY REQUIREMENTS IN ACCORDANCE WITH AMP SPECIFICATION 2, DISCOLORATION, SCRATHES, SPOTS AND OTHER COSMETIC DEFICIENCIES OF BARREL PLATING PROCESS ARE ACCEPTABLE PROVIDING PARTS PASS
A" IS VIEWED FROM MATING SIDE OF THE RECEPTACLE ASSEMBLY. S ASSEMBLED TO RECEPTACLE ASSEMBLY BEFORE SHIPMENT. A 1 IS LOCATED IN THIS ROW FOR STANDARD ORIENTAION, SEE DETAIL A. HICKNESS RANGE: .062 MAXIMUM. NG BRACKET RETAINS CONNECTOR IN .062 THICK PC BOARD WITHOUT AL HARDWARE. NALS DO NOT EXTEND BELOW COMB, THEN COMB SHALL BE PARTIALLY TD, BEFORE INSERTING CONNECTOR INTO THE PC BOARD. NG BRACKET LOCATES CONNECTOR FLUSH WITH TOP OF PC BOARD AND LOCKS BENEATH. CAL SHAPE OFFERS 180° OF SOLDERING SURFACE. AREA OF GROUNDING BRACKET BELOW PC BOARD SHALL PASS BLITY REQUIREMENTS IN ACCORDANCE WITH AMP SPECIFICATION 2, DISCOLORATION, SCRATHES, SPOTS AND OTHER COSMETIC DEFICIENCIES OF BARREL PLATING PROCESS ARE ACCEPTABLE PROVIDING PARTS PASS
S ASSEMBLED TO RECEPTACLE ASSEMBLY BEFORE SHIPMENT. 1 IS LOCATED IN THIS ROW FOR STANDARD ORIENTAION, SEE DETAIL A. HICKNESS RANGE: .062 MAXIMUM. NG BRACKET RETAINS CONNECTOR IN .062 THICK PC BOARD WITHOUT AL HARDWARE. NALS DO NOT EXTEND BELOW COMB, THEN COMB SHALL BE PARTIALLY ID, BEFORE INSERTING CONNECTOR INTO THE PC BOARD. NG BRACKET LOCATES CONNECTOR FLUSH WITH TOP OF PC BOARD AND LOCKS BENEATH. CAL SHAPE OFFERS 180° OF SOLDERING SURFACE. AREA OF GROUNDING BRACKET BELOW PC BOARD SHALL PASS BLITY REQUIREMENTS IN ACCORDANCE WITH AMP SPECIFICATION 2, DISCOLORATION, SCRATHES, SPOTS AND OTHER COSMETIC DEFICIENCIES OF BARREL PLATING PROCESS ARE ACCEPTABLE PROVIDING PARTS PASS
S ASSEMBLED TO RECEPTACLE ASSEMBLY BEFORE SHIPMENT. . 1 IS LOCATED IN THIS ROW FOR STANDARD ORIENTAION, SEE DETAIL A. HICKNESS RANGE: .062 MAXIMUM. NG BRACKET RETAINS CONNECTOR IN .062 THICK PC BOARD WITHOUT AL HARDWARE. NALS DO NOT EXTEND BELOW COMB, THEN COMB SHALL BE PARTIALLY ED, BEFORE INSERTING CONNECTOR INTO THE PC BOARD. NG BRACKET LOCATES CONNECTOR FLUSH WITH TOP OF PC BOARD AND LOCKS BENEATH. CAL SHAPE OFFERS 180° OF SOLDERING SURFACE. AREA OF GROUNDING BRACKET BELOW PC BOARD SHALL PASS BUITY REQUIREMENTS IN ACCORDANCE WITH AMP SPECIFICATION 2, DISCOLORATION, SCRATHES, SPOTS AND OTHER COSMETIC DEFICIENCIES OF BARREL PLATING PROCESS ARE ACCEPTABLE PROVIDING PARTS PASS
A 1 IS LOCATED IN THIS ROW FOR STANDARD ORIENTAION, SEE DETAIL A. HICKNESS RANGE: .062 MAXIMUM. NG BRACKET RETAINS CONNECTOR IN .062 THICK PC BOARD WITHOUT AL HARDWARE. NALS DO NOT EXTEND BELOW COMB, THEN COMB SHALL BE PARTIALLY ED, BEFORE INSERTING CONNECTOR INTO THE PC BOARD. NG BRACKET LOCATES CONNECTOR FLUSH WITH TOP OF PC BOARD AND LOCKS BENEATH. CAL SHAPE OFFERS 180° OF SOLDERING SURFACE. AREA OF GROUNDING BRACKET BELOW PC BOARD SHALL PASS BUITY REQUIREMENTS IN ACCORDANCE WITH AMP SPECIFICATION 2, DISCOLORATION, SCRATHES, SPOTS AND OTHER COSMETIC DEFICIENCIES OF BARREL PLATING PROCESS ARE ACCEPTABLE PROVIDING PARTS PASS
HICKNESS RANGE: .062 MAXIMUM. NG BRACKET RETAINS CONNECTOR IN .062 THICK PC BOARD WITHOUT AL HARDWARE. NALS DO NOT EXTEND BELOW COMB, THEN COMB SHALL BE PARTIALLY D, BEFORE INSERTING CONNECTOR INTO THE PC BOARD. NG BRACKET LOCATES CONNECTOR FLUSH WITH TOP OF PC BOARD AND LOCKS BENEATH. CAL SHAPE OFFERS 180° OF SOLDERING SURFACE. AREA OF GROUNDING BRACKET BELOW PC BOARD SHALL PASS BLITY REQUIREMENTS IN ACCORDANCE WITH AMP SPECIFICATION 2, DISCOLORATION, SCRATHES, SPOTS AND OTHER COSMETIC DEFICIENCIES OF BARREL PLATING PROCESS ARE ACCEPTABLE PROVIDING PARTS PASS
NG BRACKET RETAINS CONNECTOR IN .062 THICK PC BOARD WITHOUT AL HARDWARE. NALS DO NOT EXTEND BELOW COMB, THEN COMB SHALL BE PARTIALLY ED, BEFORE INSERTING CONNECTOR INTO THE PC BOARD. NG BRACKET LOCATES CONNECTOR FLUSH WITH TOP OF PC BOARD AND LOCKS BENEATH. CAL SHAPE OFFERS 180° OF SOLDERING SURFACE. AREA OF GROUNDING BRACKET BELOW PC BOARD SHALL PASS BLITY REQUIREMENTS IN ACCORDANCE WITH AMP SPECIFICATION 2, DISCOLORATION, SCRATHES, SPOTS AND OTHER COSMETIC DEFICIENCIES OF BARREL PLATING PROCESS ARE ACCEPTABLE PROVIDING PARTS PASS
AL HARDWARE. NALS DO NOT EXTEND BELOW COMB, THEN COMB SHALL BE PARTIALLY 20, BEFORE INSERTING CONNECTOR INTO THE PC BOARD. NG BRACKET LOCATES CONNECTOR FLUSH WITH TOP OF PC BOARD AND OCKS BENEATH. CAL SHAPE OFFERS 180° OF SOLDERING SURFACE. AREA OF GROUNDING BRACKET BELOW PC BOARD SHALL PASS BLITY REQUIREMENTS IN ACCORDANCE WITH AMP SPECIFICATION 2, DISCOLORATION, SCRATHES, SPOTS AND OTHER COSMETIC DEFICIENCIES OF BARREL PLATING PROCESS ARE ACCEPTABLE PROVIDING PARTS PASS
D, BEFORE INSERTING CONNECTOR INTO THE PC BOARD. NG BRACKET LOCATES CONNECTOR FLUSH WITH TOP OF PC BOARD AND OCKS BENEATH. CAL SHAPE OFFERS 180° OF SOLDERING SURFACE. AREA OF GROUNDING BRACKET BELOW PC BOARD SHALL PASS BLITY REQUIREMENTS IN ACCORDANCE WITH AMP SPECIFICATION 2, DISCOLORATION, SCRATHES, SPOTS AND OTHER COSMETIC DEFICIENCIES OF BARREL PLATING PROCESS ARE ACCEPTABLE PROVIDING PARTS PASS
OCKS BENEATH. CAL SHAPE OFFERS 180° OF SOLDERING SURFACE. AREA OF GROUNDING BRACKET BELOW PC BOARD SHALL PASS BLITY REQUIREMENTS IN ACCORDANCE WITH AMP SPECIFICATION 2, DISCOLORATION, SCRATHES, SPOTS AND OTHER COSMETIC DEFICIENCIES OF BARREL PLATING PROCESS ARE ACCEPTABLE PROVIDING PARTS PASS
AREA OF GROUNDING BRACKET BELOW PC BOARD SHALL PASS BLITY REQUIREMENTS IN ACCORDANCE WITH AMP SPECIFICATION 2, DISCOLORATION, SCRATHES, SPOTS AND OTHER COSMETIC DEFICIENCIES OF BARREL PLATING PROCESS ARE ACCEPTABLE PROVIDING PARTS PASS
BLITY REQUIREMENTS IN ACCORDANCE WITH AMP SPECIFICATION 2, DISCOLORATION, SCRATHES, SPOTS AND OTHER COSMETIC DEFICIENCIES OF BARREL PLATING PROCESS ARE ACCEPTABLE PROVIDING PARTS PASS
\wedge
12

	A	STANDARD	5555057-1	
	DETAIL	ORIENTATION	PART NUMBER	
CONTROLLED DOCUMENT. B. MCMASTER CHK 24A	G05 E Tyco Electronics	Tyco Electronics Corporation Harrisburg, PA 17105-3608		
	APVD 24AUG05 NAME W. MILLHIMES RECEPTACLE ASSEMBLY, 50 POSITION PRODUCT SPEC RIGHT ANGLE, SHIELDED, BAIL LOCK W/ GROUND PANEL MOUNTING			
4 PLC ±		AWING NO	RESTRICTED TO	
FINISH WEIGHT -	A1 00779 C	- 5555057	_	
CUSTOMER DRAWIN	<u>, , , , , , , , , , , , , , , , , , , </u>	SCALE 4:1 SHEE	et of rev 1 1 B	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 5555057-1