


REV. 0  
DCO 17705

COIL: @ 25°C  
 RESISTANCE 540 - 770 OHMS  
 NOMINAL VOLTAGE 26.5 VDC  
 MUST OPERATE 13.0 VDC  
 MUST RELEASE 10.1 VDC MAX., 2.3 VDC MIN.

ENVIRONMENT:  
 VIBRATION 10 Hz TO 2000 Hz @ 15 g's  
 SHOCK 100 g's 6±1 MS. DURATION  
 TEMPERATURE -65 °C TO +125 °C  
 NOTES: OPERATE & RELEASE 6 MS MAX.  
CONTACT BOUNCE 1 MS MAX.

CUSTOMER DATA SHEET



TERMINAL VIEW

CONTACT RATING: 2A 28 VDC RESISTIVE 100,000  
OPERATIONS MINIMUM

DR. ASB 13JAN04

CK [Signature] 1/13/04

**CII Technologies**  
 advanced control electronic solutions

CUST. QPL  
 CUST. NO. M5757/10-053 REV. \_\_\_\_\_

"FW" RELAY

FW 1301G02

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[FW1301G02](#)