

Specification Sheet

Part Number: 596-00247

CAUTION: SOLAR CIRCUIT

Solar Label, Reflective, CAUTION SOLAR CIRCUIT, 6.5" x 1.0", VL, Red, 50/pkg

Article Number	596-00247
Type	CSCIRLBL
Color	Red (RD)
Features & Benefits	<ul style="list-style-type: none">Made with UV-stable inks and materials for durability and weather resistance.Reflective properties to meet applicable NEC code requirements for reflective identification.Supplied with an aggressive adhesive to ensure long life.Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Quantity Per	roll

Product Description

HellermannTyton Pre-Printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code (NEC) and the International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description

Solar Label, Reflective, CAUTION SOLAR CIRCUIT, 6.5" x 1.0", VL, Red, 50/pkg

Global Part Name

CSCIRLBL-V-RD

Technical Description

Pre-Printed Reflective Solar Label, 6.5" X 1", CAUTION: SOLAR CIRCUIT, Red

Width W (Imperial)

6.5

Width W (Metric)

165.1

Thickness T (Metric)

64.0

Height H (Imperial)

1.0

Height H (Metric)

25.40

Material

Vinyl

Material Shortcut

V

Adhesive

Acrylic

Halogen free

No

Adhesive Operating Temperature

-40°F to +302°F (-40°C to +150°C)

Operating Temperature (Metric)

-40°F to +174°F (-40°C to +79°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Certification/Specification WEB

IFC 2012 UL 969 NEC2011

Warranty (US)

Yes

UL Recognized (US)

Yes

Package Quantity(Imperial)

50

Package Quantity (Metric)

50

Customs Number

3919102055

Labels per Column

1

Labels per Row

1

Weight (Metric)

0.521

Weight (Imperial)

31.97

