

Product data sheet

Characteristics

XS1N18PB349L1

inductive sensor XS1 M18 - L38.5mm - brass - Sn10mm - 12..24VDC - cable 5m



Main

Range of product	OsiSense XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Product specific application	-
Sensor name	XS1
Sensor design	Cylindrical M18
Size	38.5 mm
Body type	Fixed
Enclosure material	Nickel plated brass
Type of output signal	Discrete
Wiring technique	3-wire
[Sn] nominal sensing distance	10 mm
Discrete output function	1 NC
Discrete output type	PNP
Electrical connection	Cable
Cable length	5 m
Wire insulation material	PvR
[Us] rated supply voltage	12...24 V DC with reverse polarity protection
Switching capacity in mA	≤ 200 mA DC with overload and short-circuit protection
IP degree of protection	IP68 double insulation conforming to IEC 60529 IP69 K conforming to DIN 40050

Complementary

ISO thread	M18 x 1
Detection face	Frontal
Detector flush mounting acceptance	Flush mountable
Material	Metal
[Sd] sensing range	> 8...15 mm
Operating zone	0...8 mm
Differential travel	1...15% of Sr
Output circuit type	DC
Cable composition	3 x 0.34 mm ²
Status LED	1 LED yellow for output state
Supply voltage limits	10...36 V DC
Switching frequency	≤ 1000 Hz
Voltage drop	≤ 2 V at closed state
Current consumption	0...10 mA at no-load
Delay first up	≤ 5 ms
Delay response	≤ 0.3 ms
Delay recovery	≤ 0.7 ms
Marking	CE
Threaded length	28 mm
Length	33.5 mm
Product weight	0.1 kg 0.22 kg

Environment

Product certifications	CSA UL
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C
Vibration resistance	25 gn amplitude = +/- 2 mm (f = 10...55 Hz) conforming to IEC 60068-2-6
Shock resistance	50 gn for 11 ms conforming to IEC 60068-2-27

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[XS1N18PB349L1](#)