
PART NUMBER	SSL-LX3054IT	REV.	С
DATE	E.C.N. NUMBER AND REVISION COMMENTS		REV.
07.25.95	UPDATED SPECS.		Α
04.16.01	E.C.N. #10BRDR. & REDRAWN IN 3D.		В
10.17.11	E.C.N. #10BRDR.		С

ELECTRO-OPTICAL CH	ARACTERIS	TICS TA=25°	°C	l f= 20mA	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		635		nm	
FORWARD VOLTAGE		2.0	2.5	Vf	
REVERSE VOLTAGE	5.0			Vr	lr=100µA
AXIAL INTENSITY		45		mcd	$I_f = 20 \text{mA}$
VIEWING ANGLE		30		2x theta	
EMITTED COLOR:	RED				
EPOXY LENS FINISH:	RED TRA	NSPARENT			

A LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	- 1.6	mW/°C
OPERATING, STORAGE TEMP.	-40 TO +85	•C
SOLDERING TEMP.	+ 260	•C
2.0mm FROM BODY		3 SEC. MAX
* t<10µS		

Ø3.00 [Ø0.118] Ø4.00 [Ø0.157]



*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= $\frac{+0.00}{-0.00}$ MAX.= $\frac{+0.00}{-0.00}$ MAX

HONE: FAX: + 7	290 E. HELEN ROAD	T-3mm (T-1) 635nm RED LED, RED TRANSPARENT LENS.	DATE:	10.17.11	DRAWN BY:	AB
	PALATINE, IL 60067-6976 PHONE: +1.847.359.2790		PAGE:	1 OF 1	CHKD BY:	KF
		CONFIDENTIAL INFORMATION	SCALE:	NTS	APRVD BY:	SS
	WEB: WWW.LUMEX.COM	The information contained in this document is the property of lumex inc. Except as specifically authorized in writing by lumex inc., the holder of this document shall keep all information contained herein confidential and shall protect same in whole or in part from disclosure and dissemination to all third parties.	UNIT:	mm [INCH]	(Notes)	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: SSL-LX3054IT