



FEATURES:

- Mates with Model #'s 4771, 4772 or 4741 square pin receptacles.
- The rotating Micrograbber® Test Clip is ideal for testing surface mounted devices (SMDs), high density leads with 1.2 (0.05) spacing, and fine gauge wires 0.1 (0.004).
- Two access entries with 0.6 (.025) square pins.
- Rotating pincers grasp leads firmly.
- Extended guide tube reaches into right areas and can be bent to a 35° angle.

MATERIALS:

Insulation: Nylon

Wire: Steel

RATINGS:

Operating Temperature: +80°C. (+176°F.) Max.

Operating Voltage: 30VAC/60VDC

Current: 2 Amperes Max.

ORDERING INFORMATION: Model 5790-*

*=Color, -0 Black, -2 Red

Ordering Example: 5790-2 Color is Red

ORDERING INFORMATION: Model 5929-*

-0 Kit contains 10 Model 5790 Black clips.

-2 Kit contains 10 Model 5790 Red clips.

ORDERING INFORMATION: Model 5930

Kit contains 5 Black & 5 Red Model 5790 clips.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pomona:

[5929-2](#) [5929-0](#) [5930](#) [5790-02](#)