


LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
CE	00		A	RELEASE	09JUN10	BB	JD



- 1

MAXIMUM CONNECTOR INSERTION LOSS IS 0.5dB PLUS CABLE ATTENUATION OF 3.5dB/km AT 850nm. (SEE TABLE)
2.

PRODUCT AND PROCESSING MUST MEET REQUIREMENTS OF TEC-138-702.

0.68	50.00±0.50	[1969.0±20.0]	5-2064863-0
0.64	40.00±0.40	[1575.0±16.0]	4-2064863-0
0.64	39.00±0.39	[1535.4±15.0]	3-2064863-9
0.63	38.00±0.38	[1496.1±15.0]	3-2064863-8
0.63	37.00±0.37	[1456.7±15.0]	3-2064863-7
0.63	36.00±0.36	[1417.3±14.0]	3-2064863-6
0.62	35.00±0.35	[1377.9±14.0]	3-2064863-5
0.62	34.00±0.34	[1338.6±13.0]	3-2064863-4
0.62	33.00±0.33	[1299.2±13.0]	3-2064863-3
0.61	32.00±0.30	[1259.8±12.0]	3-2064863-2
0.61	31.00±0.30	[1220.5±12.0]	3-2064863-1
0.61	30.00±0.30	[1181.0±12.0]	3-2064863-0
0.60	29.00±0.30	[1141.7±12.0]	2-2064863-9
0.60	28.00±0.30	[1102.4±12.0]	2-2064863-8
0.59	27.00±0.30	[1063.0±12.0]	2-2064863-7
0.59	24.00±0.30	[944.9±12.0]	2-2064863-6
0.59	25.00±0.30	[984.2±12.0]	2-2064863-5
0.58	24.00±0.30	[944.9±12.0]	2-2064863-4
0.58	23.00±0.30	[905.5±12.0]	2-2064863-3
0.58	22.00±0.30	[866.1±12.0]	2-2064863-2
0.57	21.00±0.30	[826.8±12.0]	2-2064863-1
0.57	20.00±0.30	[787.0±12.0]	2-2064863-0
0.57	19.00±0.30	[748.0±12.0]	1-2064863-9
0.56	18.00±0.30	[708.7±12.0]	1-2064863-8
0.56	17.00±0.17	[669.3±7.0]	1-2064863-7
0.56	16.00±0.16	[629.9±7.0]	1-2064863-6
0.55	15.00±0.15	[590.6±6.0]	1-2064863-5
0.55	14.00±0.15	[551.2±6.0]	1-2064863-4
0.55	13.00±0.15	[511.8±6.0]	1-2064863-3
0.54	12.00±0.15	[472.4±6.0]	1-2064863-2
0.54	11.00±0.15	[433.1±6.0]	1-2064863-1
0.54	10.00±0.15	[394±6.0]	1-2064863-0
0.53	9.00±0.15	[354.6±6.0]	2064863-9
0.53	8.00±0.15	[315.0±6.0]	2064863-8
0.52	7.00±0.08	[275.6±3.0]	2064863-7
0.52	6.00±0.08	[236.2±3.0]	2064863-6
0.52	5.00±0.08	[196.9±3.0]	2064863-5
0.51	4.00±0.08	[157.5±3.0]	2064863-4
0.51	3.00±0.05	[118.1±2.0]	2064863-3
0.51	2.00±0.05	[78.7±2.0]	2064863-2
0.50	1.00±0.05	[39.4±2.0]	2064863-1
MAX IL(dB)		L METERS [INCHES]	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN
B.BRIGGS
CHK
J.DUNCAN
APVD
J.DUNCAN

09JUN2010
09JUN2010
09JUN2010

DIMENSIONS:
METERS [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± -
4 PLC ± -
ANGLES ± ± -
FINISH -

MATERIAL -

WEIGHT -

CUSTOMER DRAWING

Tyco Electronics Corporation
Harrisburg, Pa 17105-3608

NAME
CABLE ASSEMBLY, FIBER OPTIC, 2.0mm OFNR OM3, AQUA, LC DUPLEX TO SC DUPLEX

SIZE
A2

CAGE CODE
00779

DRAWING NO
2064863

RESTRICTED TO -

SCALE
NTS

SHEET
1

OF
1

REV
A

AMP 1471-9 REV 31MAR2000

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-2064863-0](#)