

Material	High Conductivity Seamless Copper Tube
Plating	Electro-Tin
Wire Size	2/0 AWG
Wire Type	Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric
Wire Strip Length	1-1/16 in.
Stud Size	1/4 in.
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.
UL Temperature Rating	90 ° C
C.S.A Certified Wire Connector	Yes
Panduit Color Code on Barrel	BLACK
Panduit Die Index No. on Barrel	P45
Alternate Industry Die Index No. () on Barrel	(13)



							PANDUIT CORP.	TINLEY PARK, ILLINOIS
							LCAN2/O-14-X Copper Lug - One-Hole, Narrow Tongue, Standard Barrel	
01	11/08	DRL	DRL		TONQUE THICKNESS WAS .13±.01			
REV	DATE	BY	CHK	DESCRIPTION		ECN	SCALE N/A	DRAWING NO / CAD FILE LCAN2_0-14-CUST

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[LCAN2/0-14-X](#)