



Please download the latest datasheet of CFWLA455KB4Y-B0 from the official website of Murata Manufacturing.

Co., Ltd.

https://www.murata.com/en-us/products/productdetail?partno=CFWLA455KB4Y-B0

CFWLA455KB4Y-B0










Appearance & Shape







Features

Note: This datasheet may be out of date

CFWLA_Y series are high selectivity ceramic filters, which consist of 6 ceramic elements connected in a ladder form. They are most suitable for digital communications and mobile telephones because of their improved GDT characteristics.

Features

- 1. High selectivity
- 2. Avariety of bandwidths are available
- 3. Excellent GDT characteristics are available within pass bandwidth.
- 4. Easily mounted on a printed circuit board
- 5. Operating temperature range: -20 to +80 (degrees C), Storage temperature range: -40 to +85 (degrees C)



Other Usage

Communication Equipment



Packaging Information

Packaging	Specifications	Minimum Order Quantity
-B0	Bulk	150

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2018/12/15

Note: This datasheet may be out of date $\underline{ \text{Please download the latest datasheet of CFWLA455KB4Y-B0 from the official website of Murata Manufacturing} \\$

 $\underline{\text{Co., Ltd.}} \\ \text{https://www.murata.com/en-us/products/productdetail?partno=CFWLA455KB4Y-B0} \\$

CFWLA455KB4Y-B0



Operating Temperature Range	-20℃ to 80℃	
Shape	Lead	
Elements	6	
Center Frequency	455.0kHz	
Center Frequency Tolerance	±1.5kHz	
Nominal Center Value	No	
6dB Bandwidth	fn±15.0kHzmin.	
Stop Bandwidth	30.0kHz	
Area of Stop Bandwidth	[within 50dB]	
Stop Band Attenuation	40dB[within fn±100kHz]	
Insertion Loss	6.0dB[at minimum loss point]	
Ripple	1.0dB[within fn±10kHz]	
GDT Deviation	30.0µs[within fn±10kHz]	
Input/Output Impedance	1500Ω	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





URL: https://www.murata.com/

Last updated :2018/12/15

CFWLA455KB4Y-B0








Frequency Characteristics

Spurious Response



Rg+R1=R2=Input/Output Impedance

Measurement Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murata:

CFWCA455KEFA001-R0 CFWLA455KB4Y-B0 CFWCA455KEFA004-R0