








Sin nuestra expresa autorización, queda terminantemente prohibida la reproducción total o parcial de este documento, así como su uso indebido y/o su exhibición o comunicación a terceros. De los infractores se exigirá el correspondiente resarcimiento de daños y perjuicios. Se reserva todos los derechos para el caso de la concesión de patente de invención o el registro de Modelo Industrial.

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts ist nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patenterteilung oder GM-Eintragung vorbehalten.

Copying of this document, and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of a utility model or design.



- 1 FOR PLASTIC PARTS (POS. 1 AND 2):
 - LENGTHS: DIN 16901/130,
 - ANGLES, FORMS: DIN 7168-m, R,
 FOR METAL PARTS (POS. 3 AND 4): DIN 7168-m,
 FOR SCREWS (POS. 5 AND 6): DIN 7981 F-H.

P/N 9 contacts version: V42254-A6000-G*09

 TE Connectivity		Maßstab
Datum: 30.08.88 Bearb: De Petter Gepr: PD Com P&SE Norm:		D-Sub housing shielded 9 contacts
TOLERANCES UNLESS OTHERWISE SPECIFIED:		V42254-A6000-G***-*-27 customer drawing number: C 1393738-1
D ECO-12-017358 22JAN13 CWR C ECO-12-008266 28AUG12 CWR Zust: Mitteilung Datum: Name:	1	page 1+ of 6

Con esta patente se reivindica el uso de este documento, así como su uso indebido y/o su exhibición o comunicación a terceros. De los infractores se exigirá el correspondiente resarcimiento de daños y perjuicios. Se reserva todos los derechos para el caso de la concesión de patente de invención o el registro de Modelo Industrial.

Weitergabe sowie Verwertung dieses Unterlage, Verwertung und Mitteilung ihres Inhalts ist nicht gestattet, soweit nicht ausdrücklich zugestanden. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patenterteilung oder G.M. Untertage vorbehalten.

Copying of this document and giving it to others and the use or communication of the contents thereof are forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of the grant of a patent or the registration of a utility model or design.

A

B

C

D

E









F

A

B

C

D



housing		dimension									
P/N	No. of contacts	A	B	C	D	E	F	G	H	J	K
V42254-A6000-											
G × 15	15					28	39,62		R3	14,5	R4,5
G × 25	25	13	14	1	7,5	41,8	53,52	6,5	R4	16	R5,5
G × 37	37					58,25	69,8				
G × 50	50	16	17,5	1,5	9,5	55,78	67,41	9,5	R5,5	20,6	R7

2) only for the 37 contacts version

1) tape only for the 15 to 37 contacts versions
drawn is the 25 contacts version

		 TE Connectivity	
		D-Sub housing	
		shielded 15 to 50 contacts	
		V42254-A6000-G***-27	
		customer drawing number: C 1393738-1	
		page 2+	
		of 6	

Datum: 30.08.88	
Bearb: De Petter	
Gepr: PD Com P&SE	
Norm:	
TOLERANCES UNLESS OTHERWISE SPECIFIED:	
D	SEE SHEET 1
Zust	Mitteilung
Datum	Name

V 4 2 2 5 4 - A 6 0 0 * - G * * *

Housing type

G plastic housing, shielded

Marking and colour of the housing

1 TE-marking, grey

2 without marking, grey


3 TE-marking, black

4 without marking, black

	wire diameter					No. of contacts - housing size	
	0	1	2	3	4		
Packaging	set 1)	4-8	4-6	6-8	4-8	09	9 contact - housing size 1
	200 2)	5-10	5-8	8-10	5-10	15	15 contacts - housing size 2
	200 2)	5-11	5-8,5	8,5-1	5-11	25	25 contacts - housing size 3
	200 2)	6-11	6-8	10-11	6-11	37	37 contacts - housing size 4
	200 2)	9-14,5	9-12	12-14,5	9-14,5	50	50 contacts - housing size 5
							1) per set, in blister - 9 and 15 contacts : 25 - 25, 37 and 50 contacts : 15 2) loose pieces, in cardboard : 200



TE Connectivity



LOC DIMENSIONS
GW IN MM

SCALE

WEIGHT

MATERIAL

NAME

D-Sub Housing

shielded

DWG NO.

V42254-A6000-G***-*-27

SHT. 3+

REV.	CHANGE ORDER	DATE	APP.
D	SEE SHEET 1		

DATE 30.08.88
NAME De Petter
DEP. PD Com P&SE
EC
TOLERANCE UNLESS
SPECIFIED OTHERWISE

customer drawing number: C 1393738-1

OF 6

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN TYCO ELECTRONICS PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA USA.

PROPRIETARY:

Old Part Number	TE Part Number		
V42254-A6000-G109	1393738-1		
V42254-A6000-G115	1393738-2		
V42254-A6000-G125	1393738-3		
V42254-A6000-G137	1393738-4		
V42254-A6000-G150	1393738-5		
V42254-A6000-G209	1393738-6	OBSOLETE	
V42254-A6000-G309	1393738-7	OBSOLETE	
V42254-A6000-G315	1393738-8	OBSOLETE	
V42254-A6000-G325	1393738-9	SUPERSEDED BY 1393738-1	
V42254-A6001-G109	4-1393738-2	OBSOLETE	
V42254-A6001-G125	4-1393738-4	SUPERSEDED BY 6-1393738-1	
V42254-A6001-G309	4-1393738-5	SUPERSEDED BY 1-1393739-9	
V42254-A6001-G315	4-1393738-6	SUPERSEDED BY 6-1393738-7	
V42254-A6002-G109	5-1393738-0	OBSOLETE	
V42254-A6002-G125	5-1393738-2	SUPERSEDED BY 6-1393738-1	
V42254-A6003-G137	5-1393738-7	SUPERSEDED BY 6-1393738-2	
V42254-A6004-G109	5-1393738-9		
V42254-A6004-G115	6-1393738-0		
V42254-A6004-G125	6-1393738-1		
V42254-A6004-G137	6-1393738-2		
V42254-A6004-G150	6-1393738-3		
V42254-A6004-G209	6-1393738-4	SUPERSEDED BY 5-1393738-9	
V42254-A6004-G215	6-1393738-5	OBSOLETE	
V42254-A6004-G225	6-1393738-6	OBSOLETE	
V42254-A6004-G309	1-1393739-9	OBSOLETE	
V42254-A6004-G315	6-1393738-7	OBSOLETE	
V42254-A6004-G325	2-1393739-0	OBSOLETE	
V42254-A6004-G337	2-1393739-1	SUPERSEDED BY 6-1393738-2	
V42254-A6004-G350	2-1393739-2	SUPERSEDED BY 6-1393738-3	
V42254-A6004-G409	6-1393738-8	OBSOLETE	
V42254-A6004-G415	6-1393738-9	OBSOLETE	
V42254-A6004-G437	7-1393738-1	OBSOLETE	



V 4 2 2 5 4 - A 6 1 * * - L 1

Technical data		
	contact tube outer diameter ±0.1	for shield braiding outer diameter
04	4	2.0 to 2.7
05	5	2.8 to 3.7
06	6	3.8 to 4.7
07	7	4.8 to 5.7
08	8	5.8 to 6.7
09	9	6.8 to 7.7
10	10	7.8 to 8.7
11	11	8.8 to 9.7
12	12	9.8 to 10.7
13	13	10.8 to 11.7
14	14	11.8 to 12.7
15	15	12.8 to 13.7

Active part numbers. Contact
Tyco Electronics for
other configuration availability

Old Part Number	TE Part Number	
V42254-A6104-L1	3-1393561-2	OBSOLETE
V42254-A6105-L1	3-1393561-3	
V42254-A6106-L1	3-1393561-4	
V42254-A6107-L1	3-1393561-5	
V42254-A6108-L1	3-1393561-6	
V42254-A6109-L1	3-1393561-9	
V42254-A6110-L1	4-1393561-0	
V42254-A6111-L1	4-1393561-1	OBSOLETE
V42254-A6112-L1	4-1393561-2	
V42254-A6113-L1	4-1393561-3	OBSOLETE
V42254-A6114-L1	4-1393561-4	OBSOLETE
V42254-A6115-L1	5-1393502-9	OBSOLETE

APPLICABLE SPEC.:				FINISH															
 TE Connectivity						DIMENSIONS APPLY		PLATING											
				SCALE		WEIGHT													
 DIMENSIONS IN MM				MATERIAL															
<table><tr><td>DATE</td><td>30.08.88</td></tr><tr><td>NAME</td><td>De Petter</td></tr><tr><td>DEP.</td><td>PD Com P&SE</td></tr><tr><td colspan="2">EC</td></tr><tr><td colspan="2">TOLERANCE UNLESS SPECIFIED OTHERWISE</td></tr></table>				DATE	30.08.88	NAME	De Petter	DEP.	PD Com P&SE	EC		TOLERANCE UNLESS SPECIFIED OTHERWISE		NAME					
				DATE	30.08.88														
				NAME	De Petter														
DEP.	PD Com P&SE																		
EC																			
TOLERANCE UNLESS SPECIFIED OTHERWISE																			
D-Sub Housing																			
D SEE SHEET 1				accessories: contact tubes															
REV. CHANGE ORDER				DWG NO.				SHT. 5+											
DATE				V42254-A6000-G***-*-27				OF 6											
APP.				customer drawing number: C 1393738-1															

V 4 2 2 5 4 - A 6 2 * * - L * * *

Technical Data			
		bushing inner diameter ±0.2	cable outer diameter
00	1) 2)	/	/
05	3)	5	4.2 to 4.9
06	3)	6	5.0 to 5.9
07	3)	7	6.0 to 6.9
08	3)	8	7.0 to 7.9
09	3)	9	8.0 to 8.9
10	2)	10	9.0 to 9.9
11	2)	11	10.0 to 10.9
12	4)	12	11.0 to 11.9
13	4)	13	12.0 to 12.9
14	4)	14	13.0 to 13.9
15	4)	15	14.0 to 14.9

	contacts	colour
1	9 to 37	grey
50	50	grey
100	9 to 37	black
150	50	black

Active part numbers. Contact Tyco Electronics for other configuration availability

Old Part Number	TE Part Number	
V42254-A6200-L 1	4-1393561-5	OBSOLETE
V42254-A6200-L 50	4-1393561-6	
V42254-A6200-L100	5-1393502-1	OBSOLETE
V42254-A6200-L150	5-1393502-2	OBSOLETE
V42254-A6205-L 1	4-1393561-7	
V42254-A6205-L100	4-1393561-8	
V42254-A6206-L 1	4-1393561-9	
V42254-A6206-L100	5-1393561-0	
V42254-A6207-L 1	5-1393561-1	
V42254-A6207-L100	5-1393561-4	OBSOLETE
V42254-A6208-L 1	5-1393561-5	
V42254-A6208-L100	5-1393561-6	OBSOLETE
V42254-A6209-L 1	5-1393561-7	
V42254-A6209-L100	5-1393561-8	
V42254-A6210-L 1	5-1393561-9	
V42254-A6210-L 50	6-1393561-0	OBSOLETE
V42254-A6210-L100	6-1393561-1	OBSOLETE
V42254-A6210-L150	5-1393502-3	OBSOLETE
V42254-A6211-L 1	6-1393561-2	
V42254-A6211-L 50	6-1393561-3	OBSOLETE
V42254-A6211-L100	5-1393502-4	OBSOLETE
V42254-A6211-L150	5-1393502-5	OBSOLETE
V42254-A6212-L 50	6-1393561-4	OBSOLETE
V42254-A6212-L150	5-1393502-6	OBSOLETE
V42254-A6213-L 50	6-1393561-5	OBSOLETE
V42254-A6213-L150	5-1393502-7	OBSOLETE
V42254-A6214-L 50	6-1393561-6	OBSOLETE
V42254-A6214-L150	5-1393502-8	OBSOLETE
V42254-A6215-L 50	8-1393501-5	OBSOLETE
V42254-A6215-L150	6-1393561-7	OBSOLETE

- 4) only for 50 contacts
3) only for 9 to 37 contacts
2) for 9 to 50 contacts
1) Blank bushing

APPLICABLE SPEC.				FINISH			
 TE Connectivity				DIMENSIONS APPLY		PLATING	
				SCALE		WEIGHT	
 DIMENSIONS IN MM				MATERIAL			
DATE 30.08.88 NAME De Petter DEP. PD Com P&SE EC TOLERANCE UNLESS SPECIFIED OTHERWISE				NAME D-Sub Housing accessories: cable bushings			
D SEE SHEET 1 REV. CHANGE ORDER DATE APP.				DWG NO. V42254-A6000-G****-27 SHT. 6 OF 6			
customer drawing number: C 1393738-1							

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[3-1393561-3](#)