
Keymodule MX

Features

The constructive design of the key and the design of the associated keycaps fulfil the ergonomic requirements for data input workstations. Long operating life with gold crosspoint contact and high reliability with quick actuation. Optionally with integrated colour LED decoupling diode or wire bridge. 4 mm actuation travel.




View of Keymodule



Drilling patterns


with fixing pins with fixing pins and with fixing pins and LED diode or wire bridge ø $1,5 \pm 0,05$ 0.0 + 0.1

Keyswitch assembly



□14 ± 0,05

Locking unit





with fixing pins


without fixing pins




Force/Travel Diagram











Multiple key mechanical


without frame







Drilling pattern 93.05 + 0.1 Modal Mine CENTER LINE OF MODULE

with frame






Cutout of frame for keycaps sizes 1x2, 1x2,25, 1x2,75



Size of keycap	1 x 2 1 x 2,25 1 x 2,75	1 x 3	1 x 8
Type of keycap	8 mm/Cyln	8 mm/Cyln	8 mm/Cyln
"A" (in mm)	23,8	38,1	133,35
Part-No. (without pins)	G99-0224	G99-0225	G99-0226
Part-No. (with pins)	G99-0742	G99-0743	G99-0744

Cutout of frame for keycaps sizes 1 x 3, 1 x 7, 1 x 8, 1 x 9, 1 x 10





Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

CHERRY:

0G99-0744 0G990742 0G990743 G99-0742 G99-0743 G99-0379 0G990224