Fair-Rite Products Corp.

Your Signal Solution®

Round Cable Snap- Its (0443800506)



Part Number: 0443800506

43 ROUND CABLE CORE ASSEMBLY

Explanation of Part Numbers: – Digits 1 & 2 = Product Class Digits 2 & 4 = Maturial Condu

- Digits 3 & 4 = Material Grade

Round cable snap- its can easily accommodate round cables or bundled wires with diameters from 2.5 mm (0.100) to 25.4 mm (1.000). These assemblies are available in four ferrite material classes to suppress differential or common- mode conducted EMI from 1 MHz into the GHz region. The polypropylene cases are meeting the RoHS restrictions of hazardous substances and have a flammability rating of UL 94 V-0.

Many of the snap- it parts have round core equivalents. See Round Cable EMI Suppression Cores.

Round Cable Snap- It Kits are available for each of the four suppression materials. 31 Snap- It Kit (0199000030), 43 Snap- It Kit (0199000031), 46 Core and Snap- It Kit (0199000032) and 61 Snap- It Kit (0199000033).


Catalog Drawing 3D Model

The B dimension is the core inside diameter.

Weight:	16	(g)
---------	----	-----

Dim	mm	mm tol	nominal inch	inch misc.
А	29.5	+/- 1.5	1.161	_
В	12.80		0.504	
С	20.6	+/- 1.0	0.811	
D	12.7	+/- 0.8	0.5	_
E	15.6	+/- 0.6	0.610	

Cable Informa	ition		
Max Diameter	Max Dimension	Solid Equivalent	Flat Cable Cores
12.8 0.504	_	2643800502	-




Typical Impedar	nce (Ω)
10 MHz	23.5
25 MHz^+	41
100 MHz^+	74
250 MHz	105

Round cable snap- it assemblies are controlled for impedances only. Minimum impedance values are specified for the + marked frequencies. The minimum impedance is listed on our catalog drawing.

Catalog Drawing

Single turn impedance tests for 31, 43 and 46 material cores are performed on the E4991A/HP4291B Impedance Analyzer. The 61 material parts are tested on the E4991A / HP4291B Impedance Analyzer and 75 material parts are tested on the E4990A Impedance Analyzer. Cores are tested with the shortest practical wire length.



CSV Download

	Fai	r- Rite Products C	orp.		One Commercia	ıl Rov	v, Wallkill, New York 125	89-02	288
888-324-7748		845-895-2055		Fax	x: 845-895-2629		ferrites@fair- rite.com		www.fair- rite.com