

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	B	PANEL MOUNTING HOLES CHANGED	23JUN16	FP	NG

NOTES

PHYSICAL PROPERTIES:

HOUSING MATERIAL: PBT

FLAMMABILITY: UL94V-0

COLOR: BLACK

MAX BOW/WARP: .0056 IN/IN.

TERMINAL:

TERMINALS: BRASS, TIN PLATED. (UNLESS OTHERWISE STATED)

SCREWS: 8-32 STEEL, NICKEL PLATED. (UNLESS OTHERWISE STATED)

Q.C. TABS: BRASS, NICKEL PLATED.

MECHANICAL:

PITCH (TERMINAL SPACING): .563"

WIRE RANGE: 10-22 AWG

RECOMMENDED TIGHTENING TORQUE: 14IN-LBS MAX.

ELECTRICAL PROPERTIES:

MAXIMUM CURRENT: 30A

OPERATING VOLTAGE: 600V



ENVIRONMENTAL PROPERTIES:

OPERATING TEMP RANGE: -40° TO +120°C

- 1

NICKEL PLATED BRASS SCREWS.
- 2

PRELIMINARY PART NUMBER.



	-	-	-	-	-	-	-	-	-	10.701	11.138	18	1-1776544-8
	-	-	-	-	-	-	-	-	-	10.138	10.575	17	1-1776544-7
	-	-	-	-	-	-	-	-	-	9.575	10.012	16	1-1776544-6
	-	-	-	-	-	-	-	-	-	9.012	9.449	15	1-1776544-5
2 1	-	-	-	-	-	-	-	-	-	8.449	8.886	14	2-1776544-4
	-	-	-	-	-	-	-	-	-	8.449	8.886	14	1-1776544-4
	-	-	-	-	-	-	-	-	-	7.886	8.323	13	1-1776544-3
	-	-	-	-	-	-	-	-	-	7.323	7.760	12	1-1776544-2
2 1	-	-	-	-	-	-	-	-	-	6.760	7.179	11	2-1776544-3
	-	-	-	-	-	-	-	-	-	6.760	7.179	11	1-1776544-1
2 1	-	-	-	-	-	-	-	-	-	6.197	6.634	10	2-1776544-2
	-	-	-	-	-	-	-	-	-	6.197	6.634	10	1-1776544-0
	-	-	-	-	-	-	-	-	-	5.634	6.071	9	1776544-9
2 1	-	-	-	-	-	-	-	-	-	5.071	5.508	8	2-1776544-5
	-	-	-	-	-	-	-	-	-	5.071	5.508	8	1776544-8
	-	-	-	-	-	-	-	-	-	4.508	4.945	7	1776544-7
2 1	-	-	-	-	-	-	-	-	-	3.945	4.382	6	2-1776544-1
	-	-	-	-	-	-	-	-	-	3.945	4.382	6	1776544-6
	-	-	-	-	-	-	-	-	-	3.382	3.819	5	1776544-5
2 1	-	-	-	-	-	-	-	-	-	2.819	3.256	4	2-1776544-0
	-	-	-	-	-	-	-	-	-	2.819	3.256	4	1776544-4
2 1	-	-	-	-	-	-	-	-	-	2.256	2.693	3	1-1776544-9
	-	-	-	-	-	-	-	-	-	2.256	2.693	3	1776544-3
	-	-	-	-	-	-	-	-	-	1.693	2.130	2	1776544-2
NOTES	8 .250 QC TAB 90° DOUBLE SIDE	7 .250 QC TAB 90°/45° DOUBLE SIDE	6 .250 QC TAB 90° DOUBLE SIDE	5 .250 QC TAB 45° DOUBLE SIDE	4 .250 QC TAB STRAIGHT DOUBLE SIDE	3 .250 QC TAB 90° SINGLE SIDE	2 .250 QC TAB 45° SINGLE SIDE	1 .250 QC TAB STRAIGHT SINGLE SIDE	DIM B	DIM A	NO. OF POSN	PART NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

MATERIAL -

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± -
1 PLC ± -
2 PLC ± -
3 PLC ± -
4 PLC ± -
ANGLES ± -
FINISH -

DWN 2/21/07
CHK 2/21/07
APVD 2/21/07
PRODUCT SPEC
APPLICATION SPEC
WEIGHT 0.000000
CUSTOMER DRAWING

TE Connectivity

14.3 (.563) DBL ROW BARRIER STRIP W/O WASHER, 600v

SIZE A2 CAGE CODE 00779 C=1776544
SCALE NTS SHEET 1 of 1 REV B

1471-9 (1/15)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-1776544-6](#)