






- 1 FOR USE WITH .093 MINIMUM THICK PRINTED CIRCUIT BOARD. REFER TO APPLICATION SPECIFICATION FOR PRINTED CIRCUIT BOARD LAYOUT DIMENSIONS AND FINISH RECOMMENDATIONS.
- 2 MOLDED PARTS: FLAME RETARDANT 94V-0 RATED GLASS FILLED, NYLON OR POLYESTER, COLOR: BLACK.
- 3 CONTACTS: COPPER ALLOY.
- 4 SHELL: CARBON STEEL.
- 5 HARDWARE: ZINC ALLOY
- 6 HARDWARE: SCREWLOCKS: CLEAR TRIVALENT CHROMATE COATING.
- 7 SHELL: BRIGHT TIN PLATED.
- 8 GOLD FLASH IN MATING AREA.
.000100 MINIMUM TIN OR TIN-LEAD ON COMPLIANT PIN.
ALL OVER .000050 MINIMUM NICKEL.
- 9 .000030 MIN GOLD IN MATING AREA.
.000100 MIN TIN OR TIN-LEAD ON COMPLIANT PIN.
ALL OVER .000050 MIN NICKEL.
OR
GOLD FLASH OVER PALLADIUM NICKEL.
.000030 MIN TOTAL IN MATING AREA.
.000100 MIN TIN OR TIN-LEAD ON COMPLIANT PIN.
ALL OVER .000050 MIN NICKEL.

		745928-2
OBSOLETE		745928-1
	CONTACT FINISH	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		OWN W LENKER 5-31-88	 TE Connectivity	
		CHK S WELDON 6-1-88		
DIMENSIONS: INCHES 		TOLERANCES, UNLESS OTHERWISE SPECIFIED: 0 PLC ± . 1 PLC ± . 2 PLC ± .005 3 PLC ± . 4 ANGLES ± 2° FINISH		
MATERIAL 		PRODUCT SPEC 108-40014 APPLICATION SPEC 114-40026 		
		WEIGHT -	SIZE A1	CASE CODE 00779
		CUSTOMER DRAWING	DRAWING NO 745928	
			SCALE 4:1	SHEET 1 OF 1
			REV S	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[745928-2](#)