



CATALOG LISTING
1CH21 - 4
PAGE 1 OF 1

REPLACES X31002

RELEASE NO. SR 11652

ISSUE 16

REVISIONS

A	CO	85348-B
B	DLM	0006144

TCC/AP
21 JUN 04

FORMTEK
DRAWN

DLM 16FEB00

CHECK SAV 16FEB00

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH

THIRD ANGLE PROJECTION

CHARACTERISTICS		ELECTRICAL DATA		SCALE FULL
OPERATING FORCE	6 - 13 LB	CONTACT ARRANGEMENT		DO NOT SCALE PRINT
FULL OVERTRAVEL FORCE	30 LB MAX	2X SPDT		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
RELEASE FORCE	4 LB MIN	LOAD	28 VDC	ONE PLACE (.0) ± .030
PRETRAVEL	.100 MAX	RES	SEA LEVEL	TWO PLACE (.00) ± .015
DIFFERENTIAL TRAVEL	.020 MIN	IND	50,000 FT.	THREE PLACE (.000) ± .005
OVERTRAVEL	.180 MIN	MOTOR		ANGLES ±
				WEIGHT 7.5 OZ MAX

NOTES

- SWITCH SEALED PER MIL-PRF-8805 SYMBOL 2
- COINCIDENCE OF OPERATING AND RELEASING POINTS: .010 OF PLUNGER TRAVEL
- CATALOG LISTING, MICRO IDENTIFICATION, CIRCUIT DIAGRAM AND DATE CODE ARE SHOWN ON NAMEPLATE
- HARDWARE MAY BE PACKAGED UNASSEMBLED PER MIL-PRF-8805

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Honeywell:](#)

[1CH21-4](#)