


LARGE INSULATION CRIMP



NOTES:

1. 'SINGLE CRIMP TO #16 & #14 AWG WIRE WITH .060"/(1.52) MAXIMUM INSULATION THICKNESS, OR DOUBLE CRIMP TO #18 AWG WIRE WITH .032"/(0.81) MAXIMUM INSULATION THICKNESS.'
2. MATERIAL: .012/(0.30) THICK C26000 BRASS.
3. FINISH: HOT TIN DIP.
4. PRODUCT SPECIFICATION : PS-44441-9999.
5. NO PORTION OF ONE LOCK TANG BEAM SHALL TOUCH ANY PORTION OF THE OTHER LOCK TANG BEAM.

CORRECT TOLERANCE EC NO: UCP2014-5466 DRWN:JDOX 2014/07/09 CHKD:ANDERSON 2014/07/09 APPR:FSMLTH 2014/07/17	QUALITY SYMBOLS ▽=0 ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
		4 PLACES ± --- ± ---	INCH	IN/MM	10:1	INCH	
		3 PLACES ± --- ± .005	ANGULAR ±1/2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	DRAWN BY	DATE	TITLE	
		2 PLACES ± 0.13 ± .01		MAB	01/03/94	TERMINAL, RECEPTACLE .125/(3.18)X.020/.51 FLAT BLADE SYSTEM - TPA	
1 PLACE ± 0.25 ± ---	CHECKED BY	DATE		molex			
0 PLACE ± ±	KBP	01/03/94	DOCUMENT NO.			SHEET NO.	
APPROVED BY	DATE	MATERIAL NO.		433751001		SD-43375-1001	1 OF 1
RAS	01/03/94	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					