

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 (818) 701-4939

1N5817 **THRU** 1N5819

Features

- Halogen free available upon request by adding suffix "-HF"
- **Guard Ring Protection**
- Low Forward Voltage
- Low Power Loss For High Efficiency
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1 Lead Free Finish/RoHS Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)

Maximum Ratings

- Operating Temperature: -55°C to +125°C Storage Temperature: -55°C to +125°C
- Maximum Thermal Resistance; 80°C/W Junction To Ambient

	MCC Part Number	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
ľ	1N5817	20V	14V	20V
I	1N5818	30V	21V	30V
I	1N5819	40V	28V	40V

Electrical Characteristics @ 25°C Unless Otherwise Specified


Average Forward Current	I _{F(AV)}	1.0A	T _A = 90°C		
Peak Forward Surge Current	I _{FSM}	25A	8.3ms, half sine		
Maximum Instantaneous Forward Voltage 1N5817 1N5818 1N5819	V _F	.45V .55V .60V	$I_{FM} = 1.0A;$ $T_J = 25^{\circ}C^{*}$		
Maximum DC Reverse Current At Rated DC Blocking Voltage	I _R	1.0mA 10mA	$T_{J} = 25^{\circ}C$ $T_{J} = 100^{\circ}C$		
Typical Reverse Recovery Time	Trr	10ns	I _F =0.5A, I _R =1.0A I _{RR} =0.25A		
Typical Junction Capacitance	C _j	110pF	Measured at 1.0MHz, V _R =4.0V		

^{*}Pulse test: Pulse width 300 µsec, Duty cycle 2%

Note:1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.

1 Amp Schottky **Barrier Rectifier** 20 to 40 Volts






DIMENSIONS							
	INCHES		MM				
DIM	MIN	MAX	MIN	MAX	NOTE		
Α	.166	.205	4.10	5.20			
В	.080	.107	2.00	2.70			
С	.028	.034	.70	.90			
D	1.000		25.40				

1N5817 thru 1N5819








Fig. 1-FORWARD CURRENT DERATING CURVEE

Fig. 2-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




Fig. 3-MAXIMUM NON-REPETITIVE SURGE CURRENT




Fig. 4-TYPICAL JUNCTION CAPACITANCE



Ordering Information:

Device	Packing	
Part Number-TP	Tape&Reel: 5Kpcs/Reel	
Part Number-AP	Ammo Packing: 5Kpcs/Ammo Box	
Part Number-BP	Bulk: 50Kpcs/Carton	

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Micro Commercial Components (MCC): 1N5817-T 1N5818-T 1N5819-T