














Control stations and enclosures

Pendant control stations, for control circuits
 Double insulated, type XAC-A
 Separate components

Contact blocks for front mounting

Description	Application	Function	Scheme	Reference	Weight kg	
 ZB2-BE101 ZB2-BE102	Single speed	N/O		ZB2-BE101	0.015	
		N/C		ZB2-BE102	0.015	
 XEN-G1191 XEN-G1491	2-speed	N/C + N/O + N/O simultaneous (1)		XEN-G1491	0.040	
		N/C + N/O + N/O staggered (1)		XEN-G1191	0.040	
 XEN-G3781 XEN-G3791	Single speed	N/O		XEN-G3781	0.060	
		N/O				
			N/O		XEN-G3791	0.060
			N/C			

Isolating switch, slow break, for front mounting

For mounting in enclosures	Application	Function	Scheme	Reference	Weight kg
 XEN-T1192	"Emergency stop"	1 N/C + N/C + N/C with positive opening operation		XEN-T1192	0.050

(1) Only for use with XAC-A9●●● operators.

(2) Not suitable for use with the following operating heads : ZA2-BB, ZA2-BD, ZA2-BG and ZA2-BS.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[XENG1191](#)