



SUPERCEDED BY
CUSTOMER PRINT
1059506

RECOMMENDED MOUNTING
HOLE
SCALE 3:1

DESIGNED FOR USE WITH .085 S.R.	
CABLE ENTRY DIAMETER MINIMUM	
HOUSING	.089
CONTACT	.0214

REVISIONS		DATE	APPROVED
REV	DESCRIPTION		
A1	REVISED PER ECO 08-020996	12/16/2008	JO

NOTES:

- CAPTURED CENTER CONTACT

.XXX = in
XX.X = mm (REF)

COMPONENT	MATERIAL	FINISH
HOUSING, OUTER MOUNTING NUT WASHER	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER QQ-P-35
RETAINING RING	STAINLESS STEEL	PASSIVATE PER QQ-P-35
HOUSING, INNER	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	GOLD PLATE PER MIL-G-45204
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
CONTACT SLEEVE	BERYLLIUM COPPER PER ASTM-B-196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
CONTACT RING	BERYLLIUM COPPER PER ASTM-B-194, ALLOY C17200, CONDITION H	GOLD PLATE PER MIL-G-45204
LOCKWASHER	CARBON STEEL 1050	NICKEL PLATE PER QQ-N-290
SPRING	MUSIC WIRE	NICKEL PLATE PER QQ-N-290

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES

FRAC.	DEC.	ANGLES
± 1/64	± .005	± 1°

These drawings and speci-
fications are the property of
M/A CDM Interconnect Div.
and shall not be reproduced
or copied or used in whole
or in part as the basis for
the manufacture or sale o
f item(s) without written
permission.

DRAWN BY J.B.	DATE 9/10/87
CHECKED BY M.H/M.	9/16/87
APP'D BY B.A.R.	9/16/87

USE ASS'Y PROCEDURE

408-04596
(45-047)
NO. AP. _____

AMP Incorporated
140 Fourth Avenue
Waltham, MA 02451-7599

TITLE DSP FLOATING PANEL
FEEDTHRU CABLE JACK
DIRECT SOLDER ATTACHMENT

SIZE B	CODE IDENT NO. 26805	4522-7985-02	REV A1
SCALE 6:1			SHEET 1 OF 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[4522-7985-02](#)