
PART NUMBER	SSL-LX100139IGW	REV.	Α
DATE	E.C.N. NUMBER AND REVISION COMMENTS		REV.
11.13.12	E.C.N. #10BRDR. & REDRAWN.		Α



ELECTRO-OPTICAL	CHARACTERISTICS	Ta=25*C If=20	lmA		
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		635(RED)		nm	
		565(GREEN)			
FORWARD VOLTAGE		2.1	2.8	Vf	
REVERSE VOLTAGE	5.0			Vr	Ir=100µA
AXIAL INTENSITY		20		mcd	If=20mA
VIEWING ANGLE		80		2x theta	
EMITTED COLOR:	RED/GREEN				
LENS FINISH:	MILKY WHITE	DIFFUSED			

LIMITS OF SAFE OPERATION AT 25°C		
PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT* (R/G)	155	mA
STEADY CURRENT (R/G)	30	mA
POWER DISSIPATION (R/G)	100	mW
DERATE FROM 25°C	-1.3	mW/°C
OPERATING TEMP.	-55 TO +100	*C
STORAGE TEMP.	-55 TO +10	*C
SOLDERING TEMP.	+260	*C
2.0mm FROM BODY	3	SEC.
* 1 × 10 C		

<sup>\*</sup> t<10µS

## RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDIER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.5 (±0.001), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN=  $^{+0.00}_{-0.00}$  MAX.=  $^{+0.00}_{-0.00}$  MAX.=  $^{+0.00}_{-0.00}$  MAX.=  $^{+0.00}_{-0.00}$  MAX.=  $^{+0.00}_{-0.000}$  MAX.=  $^{+0.000}_{-0.000}$  MAX.=  $^{+0.00$ 



CAROL STREAM, IL 60188-4900 PHONE: +1.800.278.5666 FAX: +1.630.315.2152 WEB: WWW.LUMEX.COM MEMBER OF 17W PHOTONICS GROUP T-3 1/8 (T-10) LED, BI-COLOR RED/GREEN, MILKY WHITE DIFFUSED.

\*\*THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.\*\*

CONFIDENTIAL INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. SECEPTIAL INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. SECEPTIAL VALID FOR IN PART FROM DISCLOSURE AND DESEMBATION TO ALL THIRD PARTIES.

DATE:	11.13.12	DRAWN BY:	MA
PAGE:	1 OF 1	CHKD BY:	KF
SCALE:	NTS	APRVD BY:	KF
UNIT: mm [INCH]		Pb	

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSL-LX100139IGW