

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20  
 © COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
A		REL TO ACTIVE PER ECR-08-029127	10DEC2008	DDE	DDE
AI		ECR-13-016190	180C2013	KZ	RZ

NUT, JAM  
 HOUSING, RECEPTACLE  
 ADAPTER ASSY, FIBER OPTIC DUPLEX LC

12.93  
[.509]  
 Ø28.5  
[1.122]

RECOMMENDED PANEL CUT-OUT  
 MAX PANEL THICKNESS 3.2mm

32  
[1.260]  
 HEX

GASKET, PANEL  
 2  
[.079]  
 Ø34  
[1.339]  
 19.2  
[.756]  
 29.6  
[1.165]  
 33.73  
[1.328]

⚠ MATERIAL:  
 HOUSING, RECEPTACLE: PBT, COLOR: BLACK\*  
 NUT, PANEL: BRASS, Ni PLATED  
 GASKET: SILICONE, COLOR: RED/ORANGE

LC DUPLEX ADAPTER ASSY:  
 HOUSING: PEI, COLOR: MM BEIGE, SM BLUE\*  
 PROTECTIVE COVERS: TPE, COLOR: BLACK\*  
 ALIGNMENT SLEEVES: MM METAL, SM CERAMIC

\* UL 94 V-0 RATED AT QUALIFYING THICKNESS.

2. ADAPTER PROTECTIVE COVERS ARE INCLUDED; NOT SHOWN.

3. ADAPTER SEALED PROTECTIVE CAP W/ TETHER IS ALSO AVAILABLE, P/N 1918177-1.

SINGLEMODE	1828619-2
MULTIMODE	1828619-1
DESCRIPTION	PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN D ERDMAN 19MAY2005	TE Connectivity	
DIMENSIONS: mm [IN]		CHK M GURRERI 19MAY2005		
		APVD - 19MAY2005		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME KIT, RECEPTACLE, INDUSTRIAL DUPLEX LC ODVA		
0 PLC	±0.2	PRODUCT SPEC		
1 PLC	±0.1	APPLICATION SPEC		
2 PLC	±0.1	WEIGHT		
3 PLC	±	SCALE 5:2 SHEET OF 1 REV AI		
4 PLC	±	CUSTOMER DRAWING		
ANGLES	±	SIZE CAGE CODE DRAWING NO RESTRICTED TO		
FINISH	-	A200779 C-1828619		

1471-9 (3/13)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1828619-1](#)