



FEATURES:

- Permits single or double banana plug to be used with equipment having three circuit phone jacks.
- Tip connected to hot side of adapter and ring connected to ground side.
- Sleeve. No connection.
- Cross holes 4.2 (.166) dia. in plug body provide side stackup.

MATERIALS:

Upper Conn: Binding Posts

Material: Body & Collars; Brass, Comm'l, H.H. per QQ-B-626, Alloy 360.

Finish: Nickel plated per QQ-N-290, Class 2, .0002/.0003.

Insulation: Polycarbonate molded to collars.

Color: One red, one black.

Operating Temperature: +115° C. (+239°F.) Max.

Body Insulation: Acrylonitrile – Butadiene – Styrene, molded to Binding Posts and Phone Plug.

Color: Black.

Operating Temperature: +50° C. (+122° F.) Max.

Marking: "POMONA ELECTRONICS 2112."

Lower Conn: Phone Plug, PJ-051 per MIL-P-642.

RATINGS (Entire – Assembly):

Operating Temperature: +50° C. (+122° F.) Max.

Operating Voltage: 500 VRMS.

Current: 5 Amperes Cont.

ORDERING INFORMATION: Model 2112

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Pomona:](#)

[2112](#)