



**Product:** <u>9431</u> ☑

Electronic, 20 C #22 Str TC, PVC Ins, PVC Jkt, CMG

# Request Sample

# **Product Description**

Electronic, 20 Conductor 22AWG (7x30) Tinned Copper, PVC Insulation, PVC Outer Jacket, CMG

# **Technical Specifications**

# **Physical Characteristics (Overall)**

# Conductor AWG Stranding Material No. of Conductors 22 7x30 TC - Tinned Copper 20 Conductor Count: 20

#### Insulation

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.0105 in

#### Color Chart

Black White Red Green Orange Blue White/Black Red/Black Green/Black Blue/Black Black/White Red/White Blue/White Blue/White Black/Red White/Red Orange/Red Blue/Red Red/Green	Color
Red Green Orange Blue White/Black Red/Black Green/Black Orange/Black Blue/Black Black/White Green/White Blue/White Blue/White Blue/Red White/Red Orange/Red Blue/Red	Black
Green Orange Blue White/Black Red/Black Green/Black Orange/Black Blue/Black Black/White Red/White Green/White Blue/White Black/Red White/Red Orange/Red Blue/Red	White
Orange Blue White/Black Red/Black Green/Black Orange/Black Blue/Black Black/White Red/White Green/White Blue/White Black/Red White/Red Orange/Red Blue/Red	Red
Blue White/Black Red/Black Green/Black Orange/Black Blue/Black Black/White Red/White Green/White Blue/White Black/Red White/Red Orange/Red Blue/Red	Green
White/Black Red/Black Green/Black Orange/Black Blue/Black Black/White Red/White Green/White Blue/White Black/Red White/Red Orange/Red Blue/Red	Orange
Red/Black Green/Black Orange/Black Blue/Black Black/White Red/White Green/White Blue/White Black/Red White/Red Orange/Red Blue/Red	Blue
Green/Black Orange/Black Blue/Black Black/White Red/White Green/White Blue/White Black/Red White/Red Orange/Red Blue/Red	White/Black
Orange/Black Blue/Black Black/White Red/White Green/White Blue/White Black/Red White/Red Orange/Red Blue/Red	Red/Black
Blue/Black Black/White Red/White Green/White Blue/White Black/Red White/Red Orange/Red Blue/Red	Green/Black
Black/White Red/White Green/White Blue/White Black/Red White/Red Orange/Red Blue/Red	Orange/Black
Red/White Green/White Blue/White Black/Red White/Red Orange/Red Blue/Red	Blue/Black
Green/White Blue/White Black/Red White/Red Orange/Red Blue/Red	Black/White
Blue/White Black/Red White/Red Orange/Red Blue/Red	Red/White
Black/Red White/Red Orange/Red Blue/Red	Green/White
White/Red Orange/Red Blue/Red	Blue/White
Orange/Red Blue/Red	Black/Red
Blue/Red	White/Red
	Orange/Red
Red/Green	Blue/Red
	Red/Green

# **Outer Shield Material**



#### **Outer Jacket Material**

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.345 in	0.04 in

#### **Electrical Characteristics**

#### Conductor DCR

#### Nominal Conductor DCR

15.6 Ohm/1000ft

#### Capacitance

# Nom. Capacitance Conductor to Conductor

34 pF/ft

#### Inductance

# Nominal Inductance

0.17 μH/ft

#### Current

#### Max. Recommended Current [A]

1.5 Amps per conductor @ 25°C A

# Voltage

# UL Voltage Rating

300 V RMS (CMG)

150 (UL AWM Style 2576) V RMS

#### **Temperature Range**

UL Temp Rating:	80°C (UL AWM Style 2576)
Operating Temp Range:	-20°C To +80°C

#### **Mechanical Characteristics**

Bulk Cable Weight:	82 lbs/1000ft
Max Recommended Pulling Tension:	180 lbs
Min Bend Radius/Minor Axis:	3.5 in

# **Standards**

NEC Articles:	800
NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
UL AWM Style:	UL Style 2576 (150 V 80°C)
CPR Euroclass:	Eca

# **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

# Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 FT4 Loading
CSA Flammability:	FT4
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS (CMG)

# Plenum/Non-Plenum

Plenum (Y/N):	No

#### **Part Number**

#### Variants

Item #	Color	UPC	Footnote
9431 060100	Chrome	612825245360	
9431 0601000	Chrome	612825245377	С
9431 060500	Chrome	612825245384	С
9431 0605000	Chrome	612825245391	С

C - CRATE REEL PUT-UP. Footnote:

#### **History**

Update and Revision: Revision Number: 0.220 Revision Date: 04-08-2020

#### © 2020 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.