

PRODUCT NUMBER

95228-YXXL

PLATING


3=0.76 μ m GOLD/GXT ON CONTACT AREA
2 μ m MIN MATTE TIN ON TAIL
1.27 μ m NI MIN UNDERPLATING

STYLE	SIZE	OMIT PIN POSITION
01	2x17	A5;A6;A7;A9;A10;A12;A13;A15;A16 B5;B6;B7;B9;B10;B12;B13;B15;B16

NOTES:

1. BODY MATERIAL: POLYESTER 30% GLASSFILLED COLOR BLUE FLAME RETARDANT PER UL-94 VO.
2. CONTACT MATERIAL: PHOSPHOR BRONZE.
3. 15N MIN PIN RETENTION IN EITHER DIRECTION
4. 0.6 MAX PROTRUSION PERMITTED AT 4 PLACES
5. PACKAGING :
 - POLYBAGS FROM 2 x 02 TO 2 x 06 POSITIONS
 - TUBE FROM 2 x 07 TO 2 x 36 POSITIONS
6. TO DETERMINE DIMENSIONS :
N = NUMBER OF POSITIONS PER ROW
EXAMPLE : 8 POS N x 2.54 = 20.32mm
7. RoHS COMPATIBLE PRODUCT SPECIFICATIONS

TOP VIEW




$$((N-1) \times 2.54) + 2.36$$

NOTE 6

9.34

SEE NOTE 4

EXAMPLE OF MISSING PIN



mat'l. code SEE NOTES				surface	tolerance	projection	product family
				ISO 1302	ISO 406 ISO 1101		DUBOX HDR
ltr	ecn no	dr	date	tolerances unless otherwise specified			
A	F50603	PNZ	95.08.18	angles			
B	F05-0117	LMU	05.01.31	linear			
C	F05-0244	JCO	05-09.06	.X ±0.3 .XX ±0.15 .XXX ±0.05			
D	F06-0226	LMU	06.07.11	dr	P NIZZI	95.08.18	dwg no
E	F08-0147	YOV	08.04.14	engn	JM PHAMVAN	95.08.18	sheet 1 of 1
F	B-19285	AMA	14.11.03	chr	P NIZZI	95.08.18	size
G	F-21810	AMA	15.06.19	appd	JMP	95.08.18	A3
sheet	revision						
index	sheet						

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI / Amphenol:](#)

[95228-301LF](#)