

Inline terminal - IB IL DOR LV-SET-PAC - 2861645

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Inline distance terminal, complete with accessories

Product Description

The Inline distance terminals have been designed for use within an Inline station.

Within an Inline station, a relay terminal can be used to switch voltages that are not available in the segment in which the terminal is located (e.g. switching 230 V AC within a 24 V DC segment). In this case, place a distance terminal before and after the relay terminal block. Doing so maintains the isolating distance between the individual areas.

The distance terminals interrupt the potential jumpers for the main voltage, segment voltage, ground, and functional earth ground. Lines are not connected to these terminals.



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	140.0 g
Custom tariff number	85369010
Country of origin	Germany

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	24.4 mm
Height	119.8 mm
Depth	71.5 mm

Interfaces

Connection method	Inline data jumper
Interface	Inline local bus

General

Inline terminal - IB IL DOR LV-SET-PAC - 2861645

Technical data

General

Weight	32 g
--------	------

Standards and Regulations

Test section	24 V supply (I/O) / functional earth ground 500 V AC 50 Hz 1 min.
Connection in acc. with standard	CUL

Classifications

eCl@ss

eCl@ss 4.0	27250308
eCl@ss 4.1	27250281
eCl@ss 5.0	27250304
eCl@ss 5.1	27242610
eCl@ss 6.0	27242610
eCl@ss 7.0	27242610
eCl@ss 8.0	27240692

ETIM

ETIM 2.0	EC000313
ETIM 3.0	EC001600
ETIM 4.0	EC001600
ETIM 5.0	EC002584

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / LR / BV / ABS / BSH / EAC / cULus Recognized

Inline terminal - IB IL DOR LV-SET-PAC - 2861645

Approvals

Ex Approvals

Approvals submitted

Approval details

UL Recognized 

cUL Recognized 

LR

BV

ABS

BSH

EAC

cULus Recognized 

Accessories

Accessories

Terminal marking

Inline terminal - IB IL DOR LV-SET-PAC - 2861645

Accessories


Insert strip - ESL 62X10 - 0809492



Insert strip, Sheet, white, unlabeled, can be labeled with: Office printing systems, Plotter: Laser printer, Mounting type: Insert, Lettering field: 62 x 10 mm


Drawings

Dimensional drawing




Inline terminal - IB IL DOR LV-SET-PAC - 2861645

Connection diagram



Schematic diagram



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2861645](#)