




Consult Heyco for Window Tints Other Than Clear

Heyco® Window “View Port” Plugs


Mounting Hole Diameter Range: .187” (4,7 mm) to 2.000” (50,8 mm)

- Molded of **transparent** polycarbonate for internal viewing or light transmission.
- Snap into mounting holes with fingertip pressure—no tools required.
- Multiple sizes for use in .187” (4,7 mm) to 2.000” (50,8 mm) diameter holes.
- Lock firmly into panel up to .125” (3,2 mm) thick.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Approximate Head Thickness: .062” (1,6 mm). Thickness may vary.
- **Available in a variety of tints –consult Heyco.**





MOUNTING HOLE DIAMETER		PART NO.	DESCRIPTION	PART DIMENSIONS			
in.	mm.			Clear*	A Head Diameter		B Overall Height
Single Locking Step for Panel Thickness up to .062” (1,6 mm)							
.187	4,7	1300	WP 187	.25	6,4	.23	5,9
.250	6,4	1301	WP 250	.31	7,9	.31	7,9
.312	7,9	1302	WP 312	.38	9,5		
Multiple Locking Steps for Panel Thickness up to .125” (3,2 mm)							
.375	9,5	1303	WP 375	.47	11,9	.41	10,3
.437	11,1	1304	WP 437	.53	13,5		
.500	12,7	1305	WP 500	.56	14,3		
.625	15,9	1307	WP 625	.73	18,6		
.760	19,3	1309	WP 750	.86	21,8		
.875	22,2	1311	WP 875	.95	24,2	.45	11,5
1.000	25,4	1312	WP 1000	1.13	28,6		
1.093 -	27,8 -	1313	WP 1093	1.22	30,9		
1.125	28,6						
1.375	34,9	1314	WP 1375	1.50	38,1		
1.500	38,1	1316	WP 1500	1.62	41,2		
1.750	44,5	1318	WP 1750	1.88	47,6		
2.000	50,8	1319	WP 2000	2.16	54,8		

*Consult Heyco for Window Plugs in tinted colors.



SINGLE PANEL THICKNESS DESIGN



MULTIPLE PANEL THICKNESS DESIGN



- Matte Finish diffuses light from source behind plug.

Heyco® Diffuser Plugs

MOUNTING HOLE DIAMETER*		PART NO.	DESCRIPTION	PART DIMENSIONS			
in.	mm.			Matte	A Head Diameter		B Overall Height
Multiple Locking Steps for Panel Thickness up to .125” (3,2 mm)							
.375	9,5	1303D	DWP 375	.47	11,9	.41	10,3
.760	19,3	1309D	DWP 750	.92	23,4		
1.000	25,4	1312D	DWP 1000	1.13	28,6		
2.000	50,8	1319D	DWP 2000	2.16	54,8		

*Consult Heyco for other mounting hole diameters.

Material	Polycarbonate
Flammability Rating	94V-2
Temperature Range	-40°F (-40°C) to 239°F (115°C)

Quick Specs

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Heyco:](#)

[1311](#) [1316](#) [1312](#) [1309](#) [1319](#) [1305](#) [1301](#) [1303](#) [1300](#) [1302](#) [1307](#) [1313](#) [1314](#) [1304](#) [1318](#) [1319D](#) [1309D](#)
[1312D](#) [1303D](#) [1312EE](#) [1314GJ](#) [4305AA](#)