

Low V_F Silicon Power Schottky Diode


$V_{RRM} = 40 \text{ V}$

$I_{F(AV)} = 600 \text{ A}$

Features

- High Surge Capability
- Type 40 V V_{RRM}
- Not ESD Sensitive

Twin Tower Package



Maximum ratings, at $T_j = 25^\circ\text{C}$, unless otherwise specified ("R" devices have leads reversed)

Parameter	Symbol	Conditions	MBR60040CT(R)L	Unit
Maximum recurrent peak reverse voltage	V_{RRM}		40	V
Maximum RMS voltage	V_{RMS}		28	V
Maximum DC blocking voltage	V_{DC}		40	V
Operating temperature	T_j		-55 to 150	$^\circ\text{C}$
Storage temperature	T_{stg}		-55 to 150	$^\circ\text{C}$

Electrical characteristics, at $T_j = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	MBR60040CT(R)L	Unit
Average forward current (per pkg)	I _{F(AV)}	T _C = 100 °C	600	A
Peak forward surge current (per leg)	I _{FSM}	t _p = 8.3 ms, half sine	4000	A
Maximum instantaneous forward voltage (per leg)	V _F	I _{FM} = 300 A, T _J = 25 °C	0.60	V
Maximum instantaneous reverse current at rated DC blocking voltage (per leg)	I _R	T _J = 25 °C	5	mA
		T _J = 100 °C	350	
Thermal characteristics				
Maximum thermal resistance, junction - case (per leg)	R _{θJC}		0.28	°C/W

Figure .1-Typical Forward Characteristics




Figure .2- Forward Derating Curve




Figure .4- Typical Reverse Characteristics








Figure .3- Peak Forward Surge Current



Package dimensions and terminal configuration

Product is marked with part number and terminal configuration.



DIM	Inches		Millimeters	
	Min	Max	Min	Max
A	-----	3.630	-----	92.40
B	0.700	0.800	17.78	20.32
C	-----	0.650	-----	16.51
E	0.130	0.141	3.30	3.60
F	0.482	0.490	12.25	12.45
G	1.368	BSC	34.75	BSC
N	1/4-20 UNC FULL			
Q	0.275	0.290	6.99	7.37
R	3.150	BSC	80.01	BSC
U	0.600	-----	15.24	-----
V	0.312	0.370	7.92	9.40
W	0.180	0.195	4.57	4.95

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[GeneSiC Semiconductor:](#)

[MBR60040CTL](#) [MBR60040CTRL](#)