

RJ45 connector - VS-PPC-C1-RJ45-MNNA-PG9-4Q5-B - 1405141


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



RJ45 connector, IP67, with push-pull interlocking, metal housing, CAT5e, 4-pos., with QUICKON fast connection technology, for 1-wire and 7-wire conductors AWG 26 ... 22, for cable cross section 5.0 mm ... 8.0 mm



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 325929
GTIN	4046356325929

Technical data

Mechanical characteristics

Standards/specifications	IEC PAS 61076-3-117
Number of positions	4
Connection profile	RJ45 8(4)
Locking type	Push Pull
Shielded	yes
Insertion/withdrawal cycles	≥ 500
Connection method	IDC fast connection
Conductor cross section	0.13 mm ² ... 0.32 mm ² (solid) 0.14 mm ² ... 0.36 mm ² (flexible)
Connection cross section AWG	26 ... 22 (solid) 26 ... 22 (flexible)
Max. cable diameter	5 mm ... 8 mm
External cable diameter	5 mm ... 8 mm
Cable outlet	straight
Color	silver
Degree of protection	IP65/IP67
No. of cable outlets	1

RJ45 connector - VS-PPC-C1-RJ45-MNNA-PG9-4Q5-B - 1405141

Technical data

Mechanical characteristics

Note	This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 8.2 Connectors for Outside Environment (Balanced cabling) and chapter 13 Application specific Cabling and Interconnection Technology (AIDA)
------	--

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 45 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C

Material data

Flammability rating according to UL 94	V0
Housing material	Zinc die-cast
Housing surface material	Nickel-plated
Contact carrier material	PC
Contact material	Copper alloy
Contact surface material	Gold over nickel
Material	Metal
O-ring material	NBR
Cable seal material	TPE
Material housing intermediate seal	NBR
Height	30 mm

Electrical characteristics

Number of positions	4
Nominal voltage U_N	50 V
Transmission characteristics (category)	CAT5 (IEC 11801:2002)
GRP transmission properties	CAT5 (IEC 11801:2002) CAT5 (IEC 11801:2002)
Rated current	1.75 A
Overvoltage category	I
Degree of pollution	2
Contact resistance	0.001 Ω (Wire – IDC)
	0.005 Ω (Litz wires – IDC)
Rated voltage (III/3)	72 V (DC)

Standards and Regulations

Standards/regulations	IEC PAS 61076-3-117
Flammability rating according to UL 94	V0

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50

RJ45 connector - VS-PPC-C1-RJ45-MNNA-PG9-4Q5-B - 1405141


Technical data

Environmental Product Compliance

	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
--	---

Drawings

Dimensional drawing



Push-pull RJ45 connector IP65/67

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01742
-----	--	---------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1405141](#)