

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	HI	REVISED PER ECR-16-011494	22JUN2017	NK	CX

DIM X±0.39

DIM Y

DIM Z

DIM Z

DIM W

EDGE OF BOARD

CIRCUIT 1

1 MATERIAL;
CONTACTS - BRASS.
HOUSING - UL 94V-0 RATED HIGH TEMP NYLON,
COLOR; BLACK.
HOLDDOWNS - PHOSPHOR BRONZE.

2 PLATING;
CONTACTS - 0.38µm MINIMUM GOLD OVER 2.54µm
MINIMUM NICKEL ON MATING AREA.
2.54µm TIN-LEAD MINIMUM OVER 2.54µm
NICKEL MINIMUM ON SOLDER TAIL.
HOLDDOWNS - 2.54µm TIN-LEAD.

3 DIMENSION APPLIES TO SOLDERTAIL SURFACES
AND STANDOFF SURFACES.

4 RECOMMENDED PC BOARD THICKNESS OF 1.57.

5 ALL SOLDERTAILS AND HOLDDOWNS.

6 PLATING;
CONTACTS - 0.38µm MINIMUM GOLD OVER 2.54µm
MINIMUM NICKEL ON MATING AREA.
2.54µm MATTE TIN MINIMUM OVER 2.54µm
NICKEL MINIMUM ON SOLDER TAIL.
HOLDDOWNS - 2.54µm MATTE TIN.

1.30

HOUSING

HOLDDOWN

CONTACT

CONTACT

0±0.1

0.15

7.37

-H-

11.16

15.63

STANDOFF SURFACES

DIM Z

1.27

0.635

3

DIM W

3.895

1.715

3.43±0.08 TYP

EDGE OF BOARD

1.46

10.1

5.48

5.65 MIN

EDGE OF BOARD

3 MIN

CIRCUIT 1

2.92

1.65±0.08

0.825

36.86

40.79

33.00

40.00

24

5-794628-4

33.86

37.79

30.00

37.00

22

5-794628-2

30.86

34.79

27.00

34.00

20

5-794628-0

27.86

31.79

24.00

31.00

18

4-794628-8

24.86

28.79

21.00

28.00

16

4-794628-6

21.86

25.79

18.00

25.00

14

4-794628-4

18.86

22.79

15.00

22.00

12

4-794628-2

15.86

19.79

12.00

19.00

10

4-794628-0

12.86

16.79

9.00

16.00

8

3-794628-8

9.86

13.79

6.00

13.00

6

3-794628-6

6.86

10.79

3.00

10.00

4

3-794628-4

3.86

7.79

-

7.00

2

3-794628-2

SUPERSEDED BY 5-794628-4

2

36.86

40.79

33.00

40.00

24

~~2-794628-4~~

SUPERSEDED BY 5-794628-2

2

33.86

37.79

30.00

37.00

22

~~2-794628-2~~

SUPERSEDED BY 5-794628-0

2

30.86

34.79

27.00

34.00

20

~~2-794628-0~~

SUPERSEDED BY 4-794628-8

2

27.86

31.79

24.00

31.00

18

~~1-794628-8~~

SUPERSEDED BY 4-794628-6

2

24.86

28.79

21.00

28.00

16

~~1-794628-6~~

SUPERSEDED BY 4-794628-4

2

21.86

25.79

18.00

25.00

14

~~1-794628-4~~

SUPERSEDED BY 4-794628-2

2

18.86

22.79

15.00

22.00

12

~~1-794628-2~~

SUPERSEDED BY 4-794628-0

2

15.86

19.79

12.00

19.00

10

~~1-794628-0~~

SUPERSEDED BY 3-794628-8

2

12.86

16.79

9.00

16.00

8

~~794628-8~~

SUPERSEDED BY 3-794628-6

2

9.86

13.79

6.00

13.00

6

~~794628-6~~

SUPERSEDED BY 3-794628-4

2

6.86

10.79

3.00

10.00

4

~~794628-4~~

SUPERSEDED BY 3-794628-2

2

3.86

7.79

-

7.00

2

~~794628-2~~

FINISH

DIM Y

DIM W

DIM Z

DIM X

NO. OF POSN.

PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±

1 PLC ±

2 PLC ±0.13

3 PLC ±

4 PLC ±

ANGLES ±

FINISH

SEE TABLE

DWN K. WHITAKER 19MAR2003

CHK C. JONES 19MAR2003

APVD C. JONES 19MAR2003

PRODUCT SPEC -

APPLICATION SPEC -

WEIGHT -

CUSTOMER DRAWING

TE Connectivity

NAME

SURFACE MOUNT, RIGHT ANGLE, SURFACE MOUNT HOLDDOWN, ASSEMBLY, 15 GOLD HEADER, DUAL ROW, MICRO MATE-N-LOK™

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A200779

C-794628

SCALE 4:1

SHEET 1 OF 1

REV HI

1471-9 (3/13)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[3-794628-2](#)