



- 1

REELED FOR MINI APPLICATOR.
- 2

.000030 GOLD OVER .000050 NICKEL.
- 3

GOLD FLASH OVER NICKEL, .000030 GOLD ON CONTACT AREA.
- 4

PREPLATED:(HALT).000078-.000158 BRIGHT TIN.
- 5

.000050 GOLD OVER .000050 NICKEL.
- 6

GOLD FLASH OVER NICKEL, .000015 GOLD ON CONTACT AREA.
- 7

GOLD PLATING NOT REQUIRED IN THIS AREA.
- 8

.000050 GOLD ON CONTACT AREA, GOLD FLASH AREA L OVER.000050/.000100 NICKEL ENTIRE CONTACT.
- 9

SHEARED EDGES MAY BE UNPLATED.
- 10

REELED FOR STANDARD APPLICATOR.
- 11

CUT OUTS ON BOX AT MANUFACTURER'S OPTION.
- 12

OBSOLETE PART NUMBER.
- 13

PT. OF MEAS. FOR PLATING THICKNESS(INSIDE BEAMS).
- 14

.000015 GOLD IN THE CONTACT AREA, .000050 NICKEL OVER THE ENTIRE TERMINAL.
- 15

OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI.

8	GOLD FLASH OVER NICKEL, .000015 GOLD ON CONTACT AREA.
7	GOLD PLATING NOT REQUIRED IN THIS AREA.
8	.000050 GOLD ON CONTACT AREA, GOLD FLASH AREA L OVER.000050/.000100 NICKEL ENTIRE CONTACT.
9	SHEARED EDGES MAY BE UNPLATED.
10	REELED FOR STANDARD APPLICATOR.
11	CUT OUTS ON BOX AT MANUFACTURER'S OPTION.
12	OBSOLETE PART NUMBER.

9 15	OBSOLETE		12 -7	12 -7	9 14	1-87666-9
		1- 12 -7	87667-6	8 7	1-87666-6	
		1- 12 -1	87667-5	6 7	87666-5	
		1- 12 -0	87667-4	5 7	87666-4	
		12 -9	87667-3	4	87666-3	
		12 -8	87667-2	3 7	87666-2	
		12 -7	87667-1	2 7	87666-1	
		PART NO.	LOOSE PIECE PART NO.	FINISH	1 PART NO.	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

MATERIAL

CU-NI-SI

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±	-
1 PLC	±	-
2 PLC	±	-
3 PLC	±	.005
4 PLC	±	-
ANGLES	±	-

FINISH

SEE TABLE

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN

E.C.CLAYBAUGH

8/03/98

CHK

-

APVD

-

PRODUCT SPEC

-

APPLICATION SPEC

-

WEIGHT

-

CUSTOMER DRAWING

TE Connectivity

CONTACT, FEMALE
MOD IV, CRIMP SNAP-IN

SIZE

A2

CAGE CODE

00779

DRAWING NO

C=87666

RESTRICTED TO

-

SCALE

8:1

SHEET

1 of 1

REV

R

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-87666-9](#)