



SPECIFICATIONS

| | |
|-----------------|-------------|
| Filter type | C |
| Capacitance | 3900 pF±20% |
| Working voltage | 100 V |
| Current rating | 6,5 A |

Minimum insertion loss

| FREQUENCY (MHz) | ATTENUATION (dB) |
|-----------------|------------------|
| 1 | 1 |
| 5 | 6 |
| 10 | 11 |
| 50 | 25 |
| 100 | 35 |
| 500 | 35 |
| 1000 | 32 |

Note: Jack-screws are not pre-mounted to allow mounting from any ends

| | | | | | | | | | |
|-------|----------|------|-------------------------------|----------|------|---|---|---|-------|
| | | | | Dot. | Name |  All Dim. in mm Orig. Size DIN A 4 | Male / Female D-Sub filter adapter, 15 poles, 3900 pF | Maßstab/ Scale | |
| | | | Detail. | 03/09/07 | JS | | |  | 1,5:1 |
| 34901 | 01/04/08 | BB | Insp. | | | | | | |
| 34894 | 12/03/08 | PK | Stand. | | | | TB 09 64 200 7240 | Blatt/ Page | |
| | 03/09/07 | JS | | | | | | 1 / 1 | |
| Mod. | Dot. | Name | HARTING EURL F-95972 Paris | | | | | Sub. | |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HARTING:](#)

[09642007240](#)