


UNCONTROLLED DOCUMENT

IMPEDANCE (Z)										
Frequency	25 MHz		100 MHz		300 MHz					
Nominal (REF)	85	Ω	173	Ω	295	Ω				
Minimum	_	Ω	138	Ω	_	Ω				




AGILENT E4991A Impedance/Material Analyzer HP 16092A Test Fixture

DIMENSIONS

A 14.27 [.562] ± 0.25 [.010] B 7.26 [.286] ± 0.15 [.006] C 15.24 [.600] ± 0.30 [.012]

FREQUENCY (MHz)

WEIGHT/1000 <u>8.92 kgs</u> <u>19.66 lbs</u>



		DIMENSIONS ARE IN MM [INCHES].			This print is the property of Lai	rd			
					Tech, and is loaned in confident subject to return upon request				
					with the understanding that no		Laird TECHNOLOGIES		
	F	UPDATE COMPANY LOGO	12/28/12	QIU	copies shall be made without the written consent of Laird Tech. A	ie III			
E	_	UPDATE FORMAT, ADD CURVE UPDATE	05/23/03	JRK	rights to design or invention are				
	-	Z SPECS, REM COATINGS CHG P/N FROM -00*	05/25/05		reserved.				
	D	UPDATE PRINT FORMAT	11/16/01	JRK	,		REV	DRAWN BY:	
	С	P/N WAS "000", ADD COATING SPECS.	01/08/99	BAC	28B0563-000)		LNK	
	В	UPDATED P/N FOR NEW CATALOG	12/11/95	JBE	DATE: 08/03/92 SCALE:	3 :	1	MATERIAL:	
	Α	ORIGINAL DRAFT	08/03/92	LNK	CAD # TOOL #		•	FERRITE	
	REV	DESCRIPTION	DATE	INT	28B0563-000-F	B05	63	TENNITE	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

<u>Laird</u>:

28B0563-000